

# Technical Datasheet



Trade name : FT 400  
Reviewed: 02.03.2026  
Date of print : 17.03.2026

Page : 1 of 1

## Description

FT 400 is a phosphate-free, fast-drying, low-residue cleaning agent. It is ready to use and therefore easy to apply for cleaning and degreasing heavy soiling. It evaporates from the cleaned surface almost completely. It is effective for removing oils, greases, corrosion inhibitors, forming fluids and drawing oils, adhesive residues, label residues, pigments, fresh paint residues, baked-on residues, release agents, and much more. FT 400 is easy and safe to use and is therefore ideal for degreasing surfaces before painting as an alternative to conventional solvents.

## Application

FT 400 is ready to use; simply spray it onto the surface to be cleaned, let it work briefly, and then wipe it off with a cloth or blow it off with compressed air.

Concentration recommendations (in volume%) for typical uses of the product:

Manual	100
--------	-----

Compatibility with common materials:

Steel / Stainless steel	Aluminium	Non-ferrous metals
plastics	painted surfaces	Galvanized surfaces

In the case of sensitive materials, please test the product on a sample or an inconspicuous part of the individual piece before use. If you are unsure, we will be happy to advise you. Further information on labeling, handling and disposal of the product is available from the safety data sheet.

Key to above table :

resistant	limited resistant	not resistant
-----------	-------------------	---------------

## Environmental Aspects

FT 400 contains approximately 33% by weight of VOCs\* and consists of over 99% readily biodegradable active ingredients\*\*. It is flammable, but does not burn spontaneously even at temperatures above its flash point.

\* VOCs - volatile organic compounds (according to EU definition) / \*\*Water does not count as an active ingredient

## Classification according to Regulation (EC) No.1272/2008 [CLP]

Not classified according to CLP regulation

## Transport information

No dangerous goods according to the transport guidelines

## Water hazard class (Classification according to AwSV)

Water hazard class : 1 (Slightly hazardous to water)

## Order information

- A50057-93 500 ml r-PET spray bottle
- A50057-93-BX 20x 500 ml r-PET bottle + 10x sprayer
- A02057-93 20 l Jerry can
- A20057-93 200 l Drum
- A10057-93 1000 l IBC