

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 300
Revision date : 13.08.2026
Print date : 28.08.2026

Version (Revision) : 2.0.0 (1.0.1)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

PROLAQ L 300

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Sectors of use [SU]

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Industrial uses

Products Category [PC]

PC-PNT-7 - Paint removers, thinners and related auxiliaries

Technical Functions (TF)

Cleaning agent

Uses advised against

Do not use for medical-clinical purposes.

1.3 Details of the supplier of the safety data sheet

Supplier

Bio-Circle Surface Technology GmbH

Street : Berensweg 200

Postal code/City : 33334 Gütersloh

Telephone : +49 5241 9443 0

Telefax : +49 5241 9443 44

Information contact :

Product application:

ae@bio-circle.de

Orders:

www.bio-circle.de
service@bio-circle.de

Current safety data sheet:

www.bio-circle.de [DE + EN]
service@bio-circle.de

Questions about the contents of the safety data sheet: ehs@bio-circle.de

1.4 Emergency telephone number

+49 5241 9443 51 during normal office hours

(Monday to Thursday from 8 am to 4 pm and Friday from 8 am to 3 pm)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

None

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Special rules for supplemental label elements for certain mixtures

EUH208

Contains BENZYL ALCOHOL. May produce an allergic reaction.

EUH210

Safety data sheet available on request.

2.3 Other hazards

Adverse human health effects and symptoms

This product does not contain any substance in concentrations of 0.1% or more that exhibits endocrine-disrupting properties in humans.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 300
Revision date : 13.08.2026
Print date : 28.08.2026

Version (Revision) : 2.0.0 (1.0.1)

Adverse environmental effects

This product does not contain any substance in concentrations of 0.1% or more that exhibits endocrine-disrupting properties toward non-target organisms.

This product does not contain any substance classified as a PBT or vPvB in concentrations of 0.1% or more.

This product does not contain any substance classified as a PMT or vPvM in concentrations of 0.1% or more.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

1-butylpyrrolidin-2-one ; REACH No. : 01-2120062728-48-XXXX ; EC No. : 222-437-8; CAS No. : 3470-98-2

Weight fraction : $\geq 5 - < 10 \%$

Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319

BENZYL ALCOHOL ; REACH No. : 01-2119492630-38-XXXX ; EC No. : 202-859-9; CAS No. : 100-51-6

Weight fraction : $\geq 0,5 - < 1 \%$

Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Skin Sens. 1B ; H317 Eye Irrit. 2 ; H319
(ATE - oral : 1200 mg/kg)

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation

Remove casualty to fresh air and keep warm and at rest.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Rub greasy ointment into the skin.

After eye contact

Protect uninjured eye. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion

Rinse mouth thoroughly with water. Let 1 glass of water be drunken in little sips (dilution effect). Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray jet ; alcohol resistant foam ; Extinguishing powder ; Carbon dioxide (CO₂) ; Sand

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 300
Revision date : 13.08.2026
Print date : 28.08.2026

Version (Revision) : 2.0.0 (1.0.1)

In case of fire may be liberated: Carbon monoxide , Carbon dioxide (CO₂) , Nitrogen oxides (NO_x) , Sulphur oxides

5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

5.4 Additional information

Fire transmission possible. Co-ordinate fire-fighting measures to the fire surroundings. Move undamaged containers from immediate hazard area if it can be done safely. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Special danger of slipping by leaking/spilling product. Use personal protection equipment.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3 Methods and material for containment and cleaning up

Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Wash with plenty of water. Treat the recovered material as prescribed in the section on waste disposal.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep container tightly closed.

7.2 Conditions for safe storage, including any incompatibilities

Keep/Store only in original container. Protect against : Frost .

Requirements for storage rooms and vessels

The floor should be leak tight, jointless and not absorbent.

Suitable container/equipment material: Stainless steel ; Polyethylene (PE)

Hints on joint storage

Storage class (TRGS 510) : 10

Do not store together with

Food and feedingstuffs

Further information on storage conditions

Storage temperature : 2°C - 35°C

7.3 Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

BENZYL ALCOHOL ; CAS No. : 100-51-6

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 5 ppm / 22 mg/m³

Peak limitation : 2(I)

Remark : H, Y, 11

Version : 01.09.2017

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 300
Revision date : 13.08.2026
Print date : 28.08.2026

Version (Revision) : 2.0.0 (1.0.1)

DNEL-/PNEC-values

DNEL/DNEL

1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2

Limit value type :	DNEL Consumer (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	5 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	4,29 mg/m ³
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Oral
Exposure frequency :	Long-term
Limit value :	4 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Oral
Exposure frequency :	Short-term
Limit value :	4 mg/kg bw/day
Limit value type :	DNEL worker (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	24,1 mg/m ³
Limit value type :	DNEL worker (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	10 mg/kg bw/day

BENZYL ALCOHOL ; CAS No. : 100-51-6

Limit value type :	DNEL Consumer (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	5,4 mg/m ³
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Inhalation
Exposure frequency :	Short-term
Limit value :	27 mg/m ³
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	4 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Dermal
Exposure frequency :	Short-term
Limit value :	20 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Oral
Exposure frequency :	Long-term
Limit value :	4 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Oral
Exposure frequency :	Short-term
Limit value :	20 mg/kg bw/day
Limit value type :	DNEL worker (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	22 mg/m ³

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 300
Revision date : 13.08.2026
Print date : 28.08.2026

Version (Revision) : 2.0.0 (1.0.1)

Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 110 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 8 mg/kg bw/day
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Short-term
Limit value : 40 mg/kg bw/day

PNEC

1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2

Limit value type : PNEC (Aquatic, freshwater)
Limit value : 4 mg/l
Limit value type : PNEC (Aquatic, intermittent release)
Limit value : 1 mg/l
Limit value type : PNEC (Aquatic, marine water)
Limit value : 0,4 mg/l
Limit value type : PNEC (Sediment, freshwater)
Limit value : 20,168 mg/kg dry weight
Limit value type : PNEC (Sediment, marine water)
Limit value : 2,017 mg/kg dry weight
Limit value type : PNEC (Soil)
Limit value : 1,68 mg/kg dry weight
Limit value type : PNEC (Sewage treatment plant)
Limit value : 30,62 mg/l

BENZYL ALCOHOL ; CAS No. : 100-51-6

Limit value type : PNEC (Aquatic, freshwater)
Limit value : 1 - 1,02 mg/l
Limit value type : PNEC (Aquatic, intermittent release)
Limit value : 2,3 mg/l
Limit value type : PNEC (Aquatic, marine water)
Limit value : 0,1 - 0,102 mg/l
Limit value type : PNEC (Sediment, freshwater)
Limit value : 5,27 mg/kg dw
Limit value type : PNEC (Sediment, marine water)
Limit value : 0,527 mg/kg dw
Limit value type : PNEC (Soil)
Limit value : 0,456 mg/kg soil dw
Limit value type : PNEC (Sewage treatment plant)
Limit value : 39 mg/l

8.2 Exposure controls

Personal protection equipment

Eye/face protection



Wear suitable safety goggles in case of splash.

Suitable eye protection
EN 166.

Skin protection

Hand protection

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 300
Revision date : 13.08.2026
Print date : 28.08.2026

Version (Revision) : 2.0.0 (1.0.1)



Suitable gloves type : EN 374.

Suitable material : NBR (Nitrile rubber)

Breakthrough time : 480 min.

Thickness of the glove material : 0.4 mm

Remark : The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. No tests have been performed. Selection made for preparations according to the best available knowledge and information on ingredients. In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Respiratory protection



Respiratory protection necessary at: exceeding exposure limit values

Suitable respiratory protection apparatus

Combination filtering device

Type : A P2

Remark

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (DGUV 112-190).

General information

Do not put any product-impregnated cleaning rags into your trouser pockets. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. P362+P364 - Take off contaminated clothing and wash it before reuse. P264 - Wash hands thoroughly after handling.

8.3 Additional information

The minimum requirements for safety and health protection when employees use personal protective equipment at work (89/656/EEC) must be observed.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid

Colour : clear , light yellow

Odour

pleasant ; flowery , fruity

Safety characteristics

Melting point/freezing point :	(1013 hPa)	<=	0	°C	
Initial boiling point and boiling range :	(1013 hPa)	approx.	100	°C	
Flash point :			95	°C	DIN EN ISO 2592
Auto-ignition temperature :	(Lowest value of the ingredients)		165	°C	Literature value
Flammability :			flammable		
Lower explosion limit :	(1-butylpyrrolidin-2-one)		0,9	Vol-%	Literature value
Upper explosion limit :	(BENZYL ALCOHOL)		13	Vol-%	Literature value

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 300
Revision date : 13.08.2026
Print date : 28.08.2026

Version (Revision) : 2.0.0 (1.0.1)

Vapour pressure :	(20 °C)	<	24	hPa	Calculated
Density :	(20 °C)	approx.	0,998	g/cm ³	
Water solubility :	(20 °C)		completely miscible		
pH :	(20 °C)	approx.	8,3		
Cinematic viscosity :	(20 °C)	<	30	mm ² /s	
Relative vapour density :	(20 °C)		not determined		
Maximum VOC content (2010/75/EC) :			20,9	Weight-%	
Maximum VOC content (2010/75/EC) :			208,6	g/l	
Maximum VOC content (Switzerland VOCV; SR 814.018) :			22,3	Weight-%	
Taxable VOC content (Switzerland VOCV; SR 814.018 Annex 1) :			1,6	Weight-%	

9.2 Other information

CH : This product is not under the liability for taxation of VOC acc. VOCV (<= 3 % VOC).

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non-reactive under normal use conditions.

10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

No known hazardous decomposition products.
Decomposition products in case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Acute oral toxicity

Parameter :	LD50 (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Exposure route :	Oral
Species :	Rat
Effective dose :	300 - 2000 mg/kg
Parameter :	LD50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route :	Oral
Species :	Rat
Effective dose :	1200 mg/kg

Acute dermal toxicity

Parameter :	LD50 (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 2000 mg/kg
Method :	OECD 402
Parameter :	LD50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 300
Revision date : 13.08.2026
Print date : 28.08.2026

Version (Revision) : 2.0.0 (1.0.1)

Exposure route : Dermal
Species : Rabbit
Effective dose : > 2000 mg/kg

Acute inhalation toxicity

Parameter : LC50 (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Exposure route : Inhalation (dust/mist)
Species : Rat
Effective dose : > 5,1 mg/l
Exposure time : 4 h
Method : OECD 403
Parameter : LC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route : Inhalation
Species : Rat
Effective dose : > 4178 mg/m³
Exposure time : 4 h
Method : OECD 403

Corrosion

Skin corrosion/irritation

Parameter : Skin corrosion/irritation (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Species : Albino rabbit
Result : Irritant
Method : OECD 404

Assessment/classification

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Parameter : Serious eye damage/eye irritation (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Species : Albino rabbit
Result : Causes serious eye irritation
Method : OECD 405
Parameter : Serious eye damage/eye irritation (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Species : Albino rabbit
Result : Causes serious eye irritation
Method : OECD 405

Assessment/classification

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Skin sensitisation

Parameter : Skin sensitisation (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Result : Other skin sensitiser (Subcategory 1B).
Parameter : Skin sensitisation (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Result : contact allergen according to (EC) No. 1223/2009

No further relevant information available.

Assessment/classification

EUH208 - Contains BENZYL ALCOHOL. May produce an allergic reaction.

Sensitisation to the respiratory tract

No further relevant information available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

No further relevant information available.

Germ cell mutagenicity

No further relevant information available.

Reproductive toxicity

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 300
Revision date : 13.08.2026
Print date : 28.08.2026

Version (Revision) : 2.0.0 (1.0.1)

No further relevant information available.

STOT-single exposure

No further relevant information available.

STOT-repeated exposure

No further relevant information available.

Aspiration hazard

No further relevant information available.

11.2 Information on other hazards

Endocrine disrupting properties

This product does not contain any substance in concentrations of 0.1% or more that exhibits endocrine-disrupting properties in humans.

Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Additional information

Preparation not tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter :	LC50 (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Species :	Oncorhynchus mykiss (Rainbow trout)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	> 100 mg/l
Exposure time :	96 h
Method :	OECD 203
Parameter :	LC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Species :	Pimephales promelas (fathead minnow)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	460 mg/l
Exposure time :	96 h

Chronic (long-term) fish toxicity

Parameter :	NOEC (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Species :	Pimephales promelas (fathead minnow)
Evaluation parameter :	Chronic (long-term) fish toxicity
Effective dose :	82 mg/l
Exposure time :	33 D
Method :	OECD 210

Acute (short-term) toxicity to crustacea

Parameter :	EC50 (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Species :	Daphnia magna (Big water flea)
Evaluation parameter :	Acute (short-term) daphnia toxicity
Effective dose :	> 100 mg/l
Exposure time :	48 h
Method :	OECD 202
Parameter :	EC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Species :	Daphnia magna (Big water flea)
Evaluation parameter :	Acute (short-term) toxicity to crustacea
Effective dose :	230 mg/ml
Exposure time :	48 h
Method :	OECD 202

Chronic (long-term) toxicity to aquatic invertebrate

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 300
Revision date : 13.08.2026
Print date : 28.08.2026

Version (Revision) : 2.0.0 (1.0.1)

Parameter : NOEC (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Chronic (long-term) daphnia toxicity
Effective dose : 100 mg/l
Exposure time : 21 D
Method : OECD 211
Parameter : NOEC (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Chronic (long-term) toxicity to aquatic invertebrate
Effective dose : 51 mg/l
Exposure time : 21 D
Method : OECD 211

Acute (short-term) toxicity to algae and cyanobacteria

Parameter : EC50 (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Species : Pseudokirchneriella subcapitata
Evaluation parameter : Inhibition of biomass development
Effective dose : 130 mg/l
Exposure time : 72 h
Method : OECD 201
Parameter : EC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Species : Pseudokirchneriella subcapitata
Evaluation parameter : Inhibition of growth rate
Effective dose : 770 mg/l
Exposure time : 72 h
Method : OECD 201

Chronic (long-term) toxicity to aquatic algae and cyanobacteria

Parameter : NOEC (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Species : Pseudokirchneriella subcapitata
Evaluation parameter : Inhibition of growth rate
Effective dose : 40 mg/l
Exposure time : 72 h
Method : OECD 201

Toxicity to microorganisms

Parameter : EC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Species : Toxicity to microorganisms
Effective dose : 2100 mg/l
Exposure time : 49 h

12.2 Persistence and degradability

Biodegradation

Parameter : BOD (% of ThOD) (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : 0 %
Test duration : 28 D
Evaluation : Not readily biodegradable (according to OECD criteria)
Method : OECD 301D
Parameter : BOD (% of ThOD) (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : 100 %
Test duration : 56 D
Evaluation : Biodegradable.
Method : OECD 301C
Parameter : DOC reduction (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Inoculum : Biodegradation

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 300
Revision date : 13.08.2026
Print date : 28.08.2026

Version (Revision) : 2.0.0 (1.0.1)

Evaluation parameter : Aerobic
Degradation rate : 81 %
Test duration : 112 D
Evaluation : Biodegradable.
Method : OECD 301B
Parameter : Biodegradation (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Inoculum : Biodegradation
Degradation rate : 95 - 97 %
Test duration : 21 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301A

12.3 Bioaccumulative potential

Parameter : Bioconcentration factor (BCF) (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Value : 1,37 L/kg
Parameter : Partition coefficient n-octanol/water (log value) (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Value : 1,265
Parameter : Partition coefficient n-octanol/water (log value) (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Value : 1,05
20 °C

No indication of bioaccumulation potential.

12.4 Mobility in soil

Adsorption

Parameter : Adsorption coefficient (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Inoculum : Mobility in soil
Effective dose : 43,2

12.5 Results of PBT and vPvB assessment

This product does not contain any substance classified as a PBT or vPvB in concentrations of 0.1% or more.

12.6 Endocrine disrupting properties

This product does not contain any substance in concentrations of 0.1% or more that exhibits endocrine-disrupting properties toward non-target organisms.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Waste codes/waste designations according to EWC/AVV

20 01 30 (Detergents other than those mentioned in 20 01 29)

Other disposal recommendations

Dispose of waste according to applicable legislation. Dispose of contents/container to an appropriate recycling or disposal facility. Contaminated packages must be completely emptied and can be re-used following proper cleaning (Water (with cleaning agent)). Handle contaminated packages in the same way as the substance itself.

13.2 Additional information

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

14.1 UN number or ID number

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 300
Revision date : 13.08.2026
Print date : 28.08.2026

Version (Revision) : 2.0.0 (1.0.1)

- No dangerous good in sense of these transport regulations.
- 14.2 UN proper shipping name**
No dangerous good in sense of these transport regulations.
- 14.3 Transport hazard class(es)**
No dangerous good in sense of these transport regulations.
- 14.4 Packing group**
No dangerous good in sense of these transport regulations.
- 14.5 Environmental hazards**
No dangerous good in sense of these transport regulations.
- 14.6 Special precautions for user**
None
- 14.7 Maritime transport in bulk according to IMO instruments**
No transport as bulk according to IBC Code.

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- EU legislation**
- Authorisations and/or restrictions on use**
- Restrictions on use**
Use restriction according to REACH annex XVII, no. : 40, 75
- Other regulations (EU)**
- Labelling for contents according to regulation (EC) No. 648/2004**
< 5 % non-ionic surfactants
< 5 % cationic surfactants
Contains the following substances: Benzyl Alcohol
- National regulations**
- Technische Anleitung zur Reinhaltung der Luft (TA-Luft)**
Weight fraction (Number 5.2.5. I) : < 5 %
- Water hazard class**
Classification according to AwSV - Class : 1 (Slightly hazardous to water)
- 15.2 Chemical Safety Assessment**
For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

- 16.1 Indication of changes**
01. Relevant identified uses of the substance or mixture and uses advised against · 02. Classification of the substance or mixture · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Special rules for supplemental label elements for certain mixtures · 02. Other hazards · 03. Hazardous ingredients · 05. Firefighting measures · 08. Occupational exposure limit values · 09. Information on basic physical and chemical properties · 15. Restrictions on use · 15. Technische Anleitung zur Reinhaltung der Luft (TA-Luft)
- 16.2 Abbreviations and acronyms**
ADR: Agreement concerning the International Carriage of Dangerous Goods by Road AOX: Adsorbed Organically Bound Halogens
AwSV: German Regulations on Facilities for the Handling of Substances Hazardous to Water
CAS: Chemical Abstracts Service (Department of American Chemical Society)
CLP: Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DNEL: Derived No Effect Level
ECHA: European Chemicals Agency
EINECS: European Inventory of Existing Commercial Chemical Substances
EWC/AVV: European Waste Classification Catalog / Waste List Regulation (german integration) GHS: Globally

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 300
Revision date : 13.08.2026
Print date : 28.08.2026

Version (Revision) : 2.0.0 (1.0.1)

Harmonized System of Classification and Labelling of Chemicals
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
IMDG: International Maritime Code for Dangerous Goods
IMO: International Maritime Organization
Index No.: Identification number in Annex VI of the CLP
PBT: persistent, bioaccumulative and toxic according to REACH
PMT: persistent, mobile and toxic according to REACH
PNEC: Predicted No Effect Concentration
REACH: Regulation (EC) No. 1907/2006
RID: Regulations for the International Transport of Dangerous Goods by Rail (Règlement concernant le transport international ferroviaire de marchandises dangereuses)
STEL: (Short-Term Exposure Limit)
TLV: Threshold Limit Value
TRGS: German Technical Rules for Hazardous Substances ("Technische Regel für den Umgang mit Gefahrstoffen")
TWA: Time-Weighted Average
UFI: Unique Formula Identifier
VOC: volatile organic compound
vPvB: very persistent and very bioaccumulative according to REACH
vPvM: very persistent and very mobile according to REACH
WGK: German Water Hazard Class ("Wassergefährdungsklasse")

16.3 Key literature references and sources for data

AwSV: German Regulations on Facilities for the Handling of Substances Hazardous to Water
DGUV: GESTIS-Stoffdatenbank
Directive 2004/42/EC (on the limitation of emissions of volatile organic compounds resulting from the use of organic solvents in certain paints and varnishes and in vehicle refinishing products)
Directive 2010/75/EU (on emissions from industrial and livestock farming activities)
Directive 92/85/EEC (on maternity protection)
Directive 94/33/EC (on the protection of young people at work)
EC_Safety Data Sheet of Suppliers
ECHA: Classification And Labelling Inventory
ECHA: Registered Substances
GDL: Gefahrstoffdatenbank der Länder
Industrial Safety Regulation – BetrSichV
Major Accidents Ordinance – 12th BImSchV
Regulation (EC) No 1223/2009 (on cosmetic products – Annex III)
Regulation (EC) No 2019/1021 (on persistent organic pollutants)
Regulation (EC) No 2019/1148 (on the marketing and use of explosives precursors)
Regulation (EC) No 528/2012 (on the making available on the market and use of biocidal products)
Regulation (EC) No 648/2004 (on detergents)
Regulation (EC) No 649/2012 (on the export and import of dangerous chemicals)
Regulation (EC) No. 1272/2008 of the European Parliament and of the Council Regulation (EC) No. 1907/2006
-> REGULATION (EU) 2020/878 of 18 June 2020
Technical Instructions on Air Quality Control – TA Luft
UBA Rigoletto: Wassergefährdende Stoffe

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

16.5 Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

16.6 Training advice

None

16.7 Additional information

None

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 300
Revision date : 13.08.2026
Print date : 28.08.2026

Version (Revision) : 2.0.0 (1.0.1)

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
