

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

PROLAQ L 500
UFI: 12A0-D0HP-6006-7299

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Sectors of use [SU]

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Industrial uses

Products Category [PC]

PC-PNT-7 - Paint removers, thinners and related auxiliaries

Technical Functions (TF)

Cleaning agent

1.3 Details of the supplier of the safety data sheet

Supplier

Bio-Circle Surface Technology GmbH

Street : Berensweg 200

Postal code/City : 33334 Gütersloh

Telephone : +49 5241 9443 0

Telefax : +49 5241 9443 44

Information contact :

Product application:

ae@bio-circle.de

Orders:

www.bio-circle.de
service@bio-circle.de

Current safety data sheet:

www.bio-circle.de [DE + EN]
service@bio-circle.de

Questions about the contents of the safety data sheet: ehs@bio-circle.de

1.4 Emergency telephone number

+49 5241 9443 51 during normal office hours
(Monday to Thursday from 8 am to 4 pm and Friday from 8 am to 3 pm)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Exclamation mark (GHS07)

Signal word

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

Warning

Hazard statements

H319 Causes serious eye irritation.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

2-(2-BUTOXYETHOXY)ETHANOL ; REACH No. : 01-2119475104-44-XXXX ; EC No. : 203-961-6; CAS No. : 112-34-5

Weight fraction : $\geq 10 - < 25 \%$

Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319
Substance with a common (EC) occupational exposure limit value.

2-(2-BUTOXYETHOXY)ETHYL ACETATE ; REACH No. : 01-2119475110-51-XXXX ; EC No. : 204-685-9; CAS No. : 124-17-4

Weight fraction : $\geq 10 - < 25 \%$

Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

N-BUTYL ACETATE ; REACH No. : 01-2119485493-29-XXXX ; EC No. : 204-658-1; CAS No. : 123-86-4

Weight fraction : $\geq 5 - < 10 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336 EUH066
Substance with a common (EC) occupational exposure limit value.

1-METHOXY-2-PROPANOL ; REACH No. : 01-2119457435-35-XXXX ; EC No. : 203-539-1; CAS No. : 107-98-2

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336
Substance with a common (EC) occupational exposure limit value.

Further ingredients

Reaction mass of 1,5-dimethyl glutarate, 1,6-dimethyl adipat and 1,4-dimethyl succinate ; REACH No. : 01-2119475445-32-XXXX ; EC No. : 906-170-0

Weight fraction : $\geq 50 - < 75 \%$

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation

In case of respiratory tract irritation, consult a physician.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Rub greasy ointment into the skin.

After eye contact

Protect uninjured eye. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

Rinse mouth thoroughly with water. Let 1 glass of water be drunken in little sips (dilution effect). Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Extinguishing powder Carbon dioxide (CO₂) Sand Nitrogen Extinguishing blanket

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide , Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Fire transmission possible. Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control. Apply foam in abundant quantities since some of it gets destroyed by the product. Do not allow run-off from fire-fighting to enter drains or water courses. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Special danger of slipping by leaking/spilling product. Use personal protection equipment.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3 Methods and material for containment and cleaning up

Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Wash with plenty of water. Treat the recovered material as prescribed in the section on waste disposal.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed.

7.2 Conditions for safe storage, including any incompatibilities

Keep/Store only in original container. Protect against : Frost .

Hints on joint storage

Storage class (TRGS 510) : 10

7.3 Specific end use(s)

Observe technical data sheet. Observe instructions for use.

Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

Reaction mass of 1,5-dimethyl glutarate, 1,6-dimethyl adipat and 1,4-dimethyl succinate

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 1,2 ml/m³ / 8 mg/m³
Peak limitation : 2(l)
Remark : Y
Version : 23.06.2022

2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 10 ppm / 67 mg/m³
Peak limitation : 1,5(l)
Remark : Y
Version : 23.06.2022

Limit value type (country of origin) : STEL (EC)
Limit value : 15 ppm / 101,2 mg/m³
Version : 20.06.2019

Limit value type (country of origin) : TWA (EC)
Limit value : 10 ppm / 67,5 mg/m³
Version : 20.06.2019

2-(2-BUTOXYETHOXY)ETHYL ACETATE ; CAS No. : 124-17-4

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 10 ppm / 67 mg/m³
Peak limitation : 1,5(l)
Remark : Y, 11
Version : 23.06.2022

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 62 ppm / 300 mg/m³
Peak limitation : 2(l)
Remark : Y
Version : 23.06.2022

Limit value type (country of origin) : STEL (EC)
Limit value : 150 ppm / 723 mg/m³
Version : 20.06.2019

Limit value type (country of origin) : TWA (EC)
Limit value : 50 ppm / 241 mg/m³
Version : 20.06.2019

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 100 ppm / 370 mg/m³
Peak limitation : 2(l)
Remark : Y
Version : 23.06.2022

Limit value type (country of origin) : STEL (EC)
Limit value : 150 ppm / 568 mg/m³
Remark : Skin
Version : 20.06.2019

Limit value type (country of origin) : TWA (EC)
Limit value : 100 ppm / 375 mg/m³

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

Remark : Skin
Version : 20.06.2019

Biological limit values

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

Limit value type (country of origin) : TRGS 903 (D)

Parameter : 1-methoxypropan-2-ol / Urine (U) / End of exposure or end of shift

Limit value : 15 mg/l

Version : 25.02.2022

DNEL-/PNEC-values

DNEL/DMEL

2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5

Limit value type : DNEL Consumer (systemic)

Exposure route : Oral

Exposure frequency : Long-term

Limit value : 6,25 mg/kg bw/day

Limit value type : DNEL worker (local)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 67,5 mg/m³

Limit value type : DNEL worker (local)

Exposure route : Inhalation

Exposure frequency : Short-term

Limit value : 101,2 mg/m³

2-(2-BUTOXYETHOXY)ETHYL ACETATE ; CAS No. : 124-17-4

Limit value type : DNEL Consumer (systemic)

Exposure route : Oral

Exposure frequency : Long-term

Limit value : 7,9 mg/kg

Limit value type : DNEL Consumer (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 60 mg/kg

Limit value type : DNEL Consumer (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 43 mg/m³

Limit value type : DNEL worker (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 85 mg/m³

Limit value type : DNEL worker (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 100 mg/kg

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type : DNEL Consumer (local)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 35,7 mg/m³

Limit value type : DNEL Consumer (local)

Exposure route : Inhalation

Exposure frequency : Short-term

Limit value : 300 mg/m³

Limit value type : DNEL Consumer (systemic)

Exposure route : Inhalation

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

Exposure frequency :	Long-term
Limit value :	12 mg/m ³
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Inhalation
Exposure frequency :	Short-term
Limit value :	300 mg/m ³
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	3,4 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Dermal
Exposure frequency :	Short-term
Limit value :	6 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Oral
Exposure frequency :	Long-term
Limit value :	2 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Oral
Exposure frequency :	Short-term
Limit value :	2 mg/kg bw/day
Limit value type :	DNEL worker (local)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	300 mg/m ³
Limit value type :	DNEL worker (local and systemic)
Exposure route :	Inhalation
Exposure frequency :	Short-term
Limit value :	600 mg/m ³
Limit value type :	DNEL worker (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	48 mg/m ³
Limit value type :	DNEL worker (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	7 mg/kg bw/day
Limit value type :	DNEL worker (systemic)
Exposure route :	Dermal
Exposure frequency :	Short-term
Limit value :	11 mg/kg bw/day
1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2	
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	78 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	43,9 mg/m ³
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Oral
Exposure frequency :	Long-term
Limit value :	33 mg/kg bw/day
Limit value type :	DNEL worker (local and systemic)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 553,5 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 369 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 183 mg/kg bw/day

PNEC

2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5

Limit value type : PNEC (Aquatic, freshwater)
Limit value : 1,1 mg/l
Limit value type : PNEC (Aquatic, intermittent release)
Limit value : 11 mg/l
Limit value type : PNEC (Aquatic, marine water)
Limit value : 0,11 mg/l
Limit value type : PNEC (Sediment, freshwater)
Limit value : 4,4 mg/kg dw
Limit value type : PNEC (Sediment, marine water)
Limit value : 0,44 mg/kg dw
Limit value type : PNEC (Soil)
Limit value : 0,32 mg/kg dw
Limit value type : PNEC (Secondary poisoning)
Limit value : 56 mg/kg food

2-(2-BUTOXYETHOXY)ETHYL ACETATE ; CAS No. : 124-17-4

Limit value type : PNEC (Aquatic, freshwater)
Limit value : 0,108 mg/l
Limit value type : PNEC (Aquatic, intermittent release)
Limit value : 0,6 mg/l
Limit value type : PNEC (Aquatic, marine water)
Limit value : 0,0108 mg/l
Limit value type : PNEC (Sediment, freshwater)
Limit value : 0,8 mg/kg dw
Limit value type : PNEC (Sediment, marine water)
Limit value : 0,08 mg/kg dw
Limit value type : PNEC (Soil)
Limit value : 0,29 mg/kg soil dw
Limit value type : PNEC (Secondary poisoning)
Limit value : 70 mg/kg food
Limit value type : PNEC (Sewage treatment plant)
Limit value : 100 mg/l

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type : PNEC (Aquatic, freshwater)
Limit value : 0,18 mg/l
Limit value type : PNEC (Aquatic, intermittent release)
Limit value : 0,36 mg/l
Limit value type : PNEC (Aquatic, marine water)
Limit value : 0,018 mg/l
Limit value type : PNEC (Sediment, freshwater)
Limit value : 0,981 mg/kg dw
Limit value type : PNEC (Sediment, marine water)
Limit value : 0,00981 mg/kg dw
Limit value type : PNEC (Soil)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

Limit value :	0,0903 mg/kg soil dw
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	35,6 mg/l
1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2	
Limit value type :	PNEC (Aquatic, freshwater)
Limit value :	10 mg/l
Limit value type :	PNEC (Aquatic, intermittent release)
Limit value :	100 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Limit value :	1 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Limit value :	52,3 mg/kg dw
Limit value type :	PNEC (Sediment, marine water)
Limit value :	5,2 mg/kg dw
Limit value type :	PNEC (Soil)
Limit value :	4,59 mg/kg dw
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	100 mg/l

8.2 Exposure controls

Personal protection equipment

Eye/face protection



Wear suitable safety goggles in case of splash.

Suitable eye protection
EN 166.

Skin protection

Hand protection



Suitable gloves type : EN 374.

Suitable material : Butyl caoutchouc (butyl rubber) , NBR (Nitrile rubber)

Breakthrough time : 480 min.

Thickness of the glove material : 0,7 mm

Remark : The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Respiratory protection



Respiratory protection necessary at: exceeding exposure limit values

Suitable respiratory protection apparatus

Combination filtering device

Type : A

Remark

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (DGUV 112-190).

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

General information

Do not put any product-impregnated cleaning rags into your trouser pockets. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. P362+P364 - Take off contaminated clothing and wash it before reuse. P264 - Wash hands thoroughly after handling.

8.3 Additional information

No tests have been performed. Selection made for preparations according to the best available knowledge and information on ingredients. In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid

Colour : colourless

Odour

like: Ether ; fruity , sweetish

Safety characteristics

Melting point/freezing point :	(1013 hPa)	<	-20 °C	
Initial boiling point and boiling range :	(1013 hPa)	approx.	175 °C	
Flash point :			61 - 65 °C	DIN EN ISO 13736
Auto-ignition temperature :	(2-(2-BUTOXYETHOXY)ETHANOL)		225 °C	Literature value
Flammability :			flammable	
Lower explosion limit :	(2-(2-BUTOXYETHOXY)ETHANOL)		0,7 Vol-%	Literature value
Upper explosion limit :	(2-(2-BUTOXYETHOXY)ETHANOL)		5,9 Vol-%	Literature value
Vapour pressure :	(20 °C)	<	2 hPa	Calculated
Density :	(20 °C)		1,02 g/cm ³	
Water solubility :	(20 °C)		Immiscible	
pH :	(20 °C)		not applicable	
Cinematic viscosity :	(20 °C)	<	30 mm ² /s	
Relative vapour density :	(20 °C)		not determined	
Maximum VOC content (2010/75/EC) :			8,4 Weight-%	
Maximum VOC content (2010/75/EC) :			85,7 g/l	
Maximum VOC content (Switzerland) :			82,8 Weight-%	
Taxable VOC content (Switzerland) :			29,1 Weight-%	

9.2 Other information

Not sustaining combustion. UN Test L.2: Sustained combustibility test

SECTION 10: Stability and reactivity

10.1 Reactivity

Reactions with strong oxidants are expected. Peroxides can be produced.

10.2 Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Avoid high temperatures or direct sunlight.

10.5 Incompatible materials

Oxidizing agent.

10.6 Hazardous decomposition products

No known hazardous decomposition products.
Decomposition products in case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Acute oral toxicity

Parameter :	ATEmix
Exposure route :	Oral
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route :	Oral
Species :	Mouse
Effective dose :	5530 mg/kg
Method :	OECD 401
Parameter :	LD50 (2-(2-BUTOXYETHOXY)ETHYL ACETATE ; CAS No. : 124-17-4)
Exposure route :	Oral
Species :	Rat
Effective dose :	11920 mg/kg
Parameter :	LD50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route :	Oral
Species :	Rat
Effective dose :	14 g/kg
Parameter :	LD50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route :	Oral
Species :	Rabbit
Effective dose :	7,4 g/kg
Parameter :	LD50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route :	Oral
Species :	Rat
Effective dose :	3739 - 4277 mg/kg

Acute dermal toxicity

Parameter :	ATEmix
Exposure route :	Dermal
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	2764 mg/kg
Method :	OECD 402
Parameter :	LD50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 2000 mg/kg
Method :	Regulation (EC) No. 440/2008, Annex B.3

Acute inhalation toxicity

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

Parameter : ATEmix
Exposure route : Inhalation
Effective dose : > 20 mg/l
Parameter : LC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route : Inhalation
Species : Rat
Effective dose : > 21 mg/l
Exposure time : 4 h
Method : OECD 403
Parameter : LC50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route : Inhalation
Species : Mouse
Effective dose : 6000 - 7000 ppm
Exposure time : 6 h
Method : OECD 403

Corrosion

Skin corrosion/irritation

No further relevant information available.

Serious eye damage/eye irritation

Parameter : Serious eye damage/eye irritation (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Species : Rabbit
Result : Causes serious eye irritation
Parameter : Serious eye damage/eye irritation (2-(2-BUTOXYETHOXY)ETHYL ACETATE ; CAS No. : 124-17-4)
Result : Causes serious eye irritation

Assessment/classification

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

No further relevant information available.

Sensitisation to the respiratory tract

No further relevant information available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

No further relevant information available.

Germ cell mutagenicity

No further relevant information available.

Reproductive toxicity

No further relevant information available.

STOT-single exposure

No further relevant information available.

STOT SE 3

Parameter : STOT SE 3 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Result : May cause drowsiness or dizziness.
Parameter : STOT SE 3 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route : Inhalative
Result : May cause drowsiness or dizziness.

Narcotic effects

Assessment/classification

Based on available data, the classification criteria are not met.

STOT-repeated exposure

No further relevant information available.

Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

Aspiration hazard

No further relevant information available.

11.2 Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Other adverse effects

Frequently or prolonged contact with skin may cause dermal irritation. Has degreasing effect on the skin.

Additional information

Preparation not tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter :	LC50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Species :	Lepomis macrochirus (Bluegill)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	1300 mg/l
Exposure time :	96 h
Method :	OECD 203
Parameter :	LC50 (2-(2-BUTOXYETHOXY)ETHYL ACETATE ; CAS No. : 124-17-4)
Species :	Danio rerio (zebrafish)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	50 - 70 mg/l
Exposure time :	96 h
Method :	OECD 203
Parameter :	LC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species :	Pimephales promelas (fathead minnow)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	18 mg/l
Exposure time :	96 h
Method :	OECD 203
Parameter :	LC50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Species :	Pimephales promelas (fathead minnow)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	20800 mg/l
Exposure time :	96 h

Acute (short-term) toxicity to crustacea

Parameter :	EC50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Species :	Daphnia magna (Big water flea)
Evaluation parameter :	Acute (short-term) toxicity to crustacea
Effective dose :	> 100 mg/l
Exposure time :	48 h
Method :	OECD 202
Parameter :	LC50 (2-(2-BUTOXYETHOXY)ETHYL ACETATE ; CAS No. : 124-17-4)
Species :	Daphnia magna (Big water flea)
Evaluation parameter :	Acute (short-term) daphnia toxicity
Effective dose :	665 mg/l
Exposure time :	48 h

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

Parameter : EC50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : 21100 - 25900 mg/l
Exposure time : 48 h

Chronic (long-term) toxicity to aquatic invertebrate

Parameter : NOEC (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Chronic (long-term) daphnia toxicity
Effective dose : 23 mg/l
Exposure time : 21 D

Method : OECD 211

Parameter : NOEC (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species : Desmodesmus subspicatus
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : 200 mg/l
Exposure time : 72 h

Acute (short-term) toxicity to algae and cyanobacteria

Parameter : EC50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Species : Scenedesmus subspicatus
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria
Effective dose : > 100 mg/l
Exposure time : 48 h
Method : OECD 201

Parameter : EC50 (2-(2-BUTOXYETHOXY)ETHYL ACETATE ; CAS No. : 124-17-4)
Species : Pseudokirchneriella subcapitata
Evaluation parameter : Inhibition of biomass development
Effective dose : 520 mg/l
Exposure time : 72 h
Method : DIN 38412 / part 9

Parameter : EC0 (2-(2-BUTOXYETHOXY)ETHYL ACETATE ; CAS No. : 124-17-4)
Species : Pseudokirchneriella subcapitata
Evaluation parameter : Inhibition of biomass development
Effective dose : 300 mg/l
Exposure time : 72 h

Parameter : EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species : Pimephales promelas (fathead minnow)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : 18 mg/l
Exposure time : 96 h
Method : OECD 203

Parameter : EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species : Daphnia
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : 44 mg/l
Exposure time : 48 h

Parameter : EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Chronic (long-term) daphnia toxicity
Effective dose : 34 mg/l
Exposure time : 21 D
Method : OECD 211

Parameter : EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species : Desmodesmus subspicatus
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : 674,7 mg/l

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

Exposure time : 72 h
Parameter : EC50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Species : Pseudokirchneriella subcapitata
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : > 1000 mg/l
Exposure time : 7 D

Toxicity to microorganisms

Parameter : EC10 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Species : Toxicity to microorganisms
Effective dose : > 1995 mg/l
Exposure time : 30 min
Parameter : EC0 (2-(2-BUTOXYETHOXY)ETHYL ACETATE ; CAS No. : 124-17-4)
Species : Bacteria toxicity
Effective dose : 1575 mg/l
Exposure time : 30 min
Parameter : EC50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Species : Pseudomonas putida
Evaluation parameter : Bacteria toxicity
Effective dose : > 10000 mg/l
Exposure time : 17 h
Method : DIN 38412 / part 8

12.2 Persistence and degradability

Biodegradation

Parameter : BOD (% of COD) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : 95 %
Test duration : 28 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301C
Parameter : BOD (% of ThOD) (2-(2-BUTOXYETHOXY)ETHYL ACETATE ; CAS No. : 124-17-4)
Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : 100 %
Test duration : 28 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301C
Parameter : BOD (% of COD) (2-(2-BUTOXYETHOXY)ETHYL ACETATE ; CAS No. : 124-17-4)
Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : 73 %
Test duration : 20 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301D
Parameter : CO2 formation (% of the theoretical value) (2-(2-BUTOXYETHOXY)ETHYL ACETATE ; CAS No. : 124-17-4)
Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : 102 %
Test duration : 20 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301B
Parameter : Biodegradation (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Inoculum : Biodegradation
Evaluation parameter : Aerobic

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

Degradation rate : 83 %
Test duration : 20 D
Evaluation : Readily biodegradable (according to OECD criteria).
Parameter : DOC reduction (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : 96 %
Test duration : 28 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301E

12.3 Bioaccumulative potential

Parameter : Partition coefficient n-octanol/water (log value) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Value : 1
20 °C
Method : OECD 117
Parameter : Partition coefficient n-octanol/water (log value) (2-(2-BUTOXYETHOXY)ETHYL ACETATE ; CAS No. : 124-17-4)
Value : 1,7
20 °C
Method : OECD 117
Parameter : Log KOW (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Partition coefficient n-octanol/water (log value)
Value : 1,82 - 2,3
25 °C
Parameter : Partition coefficient n-octanol/water (log value) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Value : 0,37
20 °C

No indication of bioaccumulation potential.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Waste codes/waste designations according to EWC/AVV

08 01 17 * - Waste from paint or varnish removal containing organic solvents or other dangerous substances.
20 01 29* (Detergents containing hazardous substances)

Other disposal recommendations

Dispose of waste according to applicable legislation. Dispose of contents/container to an appropriate recycling or disposal facility. Contaminated packages must be completely emptied and can be re-used following proper cleaning (Water (with cleaning agent)). Handle contaminated packages in the same way as the substance itself.

13.2 Additional information

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

industry and process.

SECTION 14: Transport information

14.1 UN number or ID number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Use restriction according to REACH annex XVII, no. : 3, 30, 40, 55, 75

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

National regulations

Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : < 5 %

Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

15.2 Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

09. Information on basic physical and chemical properties

16.2 Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (Europäisches Übereinkommen über die Beförderung gefährlicher Güter auf der Straße)

AOX: adsorbierbare organisch gebundene Halogene

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

CAS: Chemical Abstracts Service (Unterabteilung der American Chemical Society)

CLP: Verordnung (EG) Nr. 1272/2008 über die Einstufung, Kennzeichnung und Verpackung von Stoffen und Gemischen (Classification Labelling and Packaging)

EAK / AVV: europäischer Abfallartenkatalog / Abfallverzeichnis-Verordnung

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 14.04.2026
Print date : 14.04.2026

Version (Revision) : 5.1.1 (5.1.0)

ECHA: Europäische Chemikalienagentur (European Chemicals Agency)
EINECS: : Altstoffverzeichnis (European Inventory of Existing Commercial Chemical Substances)
GHS: Global harmonisiertes System zur Einstufung und Kennzeichnung von Chemikalien (Globally Harmonized System of Classification and Labelling of Chemicals)
IATA: Internationale Luftverkehrs-Vereinigung (International Air Transport Association)
ICAO: Internationale Zivilluftfahrtorganisation (International Civil Aviation Organization)
IMDG: Gefahrgutkennzeichnung für gefährliche Güter im Seeschiffverkehr (International Maritime Code for Dangerous Goods)
RID: Regelung zur internationalen Beförderung gefährlicher Güter im Schienenverkehr (Règlement concernant le transport international ferroviaire de marchandises dangereuses)
TRGS: Technische Regel für den Umgang mit Gefahrstoffen
VbF: Verordnung über brennbare Flüssigkeiten
VOC: flüchtige organische Verbindung (volatile organic compound)
VVEA: Verordnung über die Vermeidung und die Entsorgung von Abfällen
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe
WGK: Wassergefährdungsklasse

16.3 Key literature references and sources for data

DGUV: GESTIS-Stoffdatenbank
ECHA: Classification And Labelling Inventory
ECHA: Pre-registered Substances
ECHA: Registered Substances
EC_Safety Data Sheet of Suppliers
ESIS: European Chemical Substances Information System
GDL: Gefahrstoffdatenbank der Länder
UBA Rigoletto: Wassergefährdende Stoffe
Regulation (EC) No. 1907/2006 of the European Parliament and of the Council
]-> COMMISSION REGULATION (EU) 2020/878 of 18 June 2020
Regulation (EC) No. 1272/2008 of the European Parliament and of the Council

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].
Evaluation :
Eye Irrit. 2 : Calculation method.

16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.