

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

Stripper  
UFI: EV30-X0U3-400J-KGAN

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses**

**Products Category [PC]**

PC-PNT-7 - Paint removers, thinners and related auxiliaries

### 1.3 Details of the supplier of the safety data sheet

**Supplier**

Bio-Circle Surface Technology GmbH

**Street :** Berensweg 200

**Postal code/City :** 33334 Gütersloh

**Telephone :** +49 5241 9443 0

**Telefax :** +49 5241 9443 44

**Information contact :** labor@bio-circle.de

### 1.4 Emergency telephone number

+49 5241 9443 51 during normal office hours  
(Monday to Thursday from 8 am to 4 pm and Friday from 8 am to 3 pm)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

### 2.2 Label elements

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



Corrosion (GHS05) · Exclamation mark (GHS07)

**Signal word**

Danger

**Hazard components for labelling**

BENZYL ALCOHOL ; CAS No. : 100-51-6

Oxirane, methyl-, polymer with oxirane, mono(2-propylheptyl) ether ; CAS No. : 166736-08-9

QUATERNARY AMMONIA COMPOUNDS ; CAS No. : 863679-20-3

DISODIUM METASILICATE ; CAS No. : 6834-92-0

**Hazard statements**

H318 Causes serious eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

## Precautionary statements

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER or doctor/physician.  
P302+P352 IF ON SKIN: Wash with plenty of water/....  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

## 2.3 Other hazards

None

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

BENZYL ALCOHOL ; REACH No. : 01-2119492630-38-XXXX ; EC No. : 202-859-9; CAS No. : 100-51-6

Weight fraction :  $\geq 10 - < 25$  %  
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Skin Sens. 1B ; H317 Eye Irrit. 2 ; H319  
(ATE - oral : 1200 mg/kg)

2-(2-BUTOXYETHOXY)ETHANOL ; REACH No. : 01-2119475104-44-XXXX ; EC No. : 203-961-6; CAS No. : 112-34-5

Weight fraction :  $\geq 10 - < 25$  %  
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319  
Substance with a common (EC) occupational exposure limit value.

POTASSIUM CUMENESULFONATE ; REACH No. : 01-2119489427-24-XXXX ; EC No. : 629-764-9; CAS No. : 164524-02-1

Weight fraction :  $\geq 1 - < 5$  %  
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

SODIUM CUMENESULPHONATE ; REACH No. : 01-2119489411-37-XXXX ; EC No. : 239-854-6; CAS No. : 15763-76-5

Weight fraction :  $\geq 1 - < 5$  %  
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

ISOTRIDECANOL, ETHOXYLATED ( $\geq 2.5$ ) ; REACH No. : (Polymer) ; EC No. : 931-138-8; CAS No. : 9043-30-5

Weight fraction :  $\geq 1 - < 5$  %  
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Aquatic Chronic 3 ; H412  
Specific Conc. Limits : Eye Dam. 1 ; H318: C  $\geq 10,01$  %

C9-C11, ALCOHOLS, ETHOXYLATED (4 EO) ; REACH No. : 01-2119980051-45-XXXX ; EC No. : 614-482-0; CAS No. : 68439-46-3

Weight fraction :  $\geq 1 - < 5$  %  
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

ALCOHOLS, ETHOXYLATED, C9-C11 (5.5 EO) ; REACH No. : 01-2119980051-45-XXXX ; EC No. : 614-482-0; CAS No. : 68439-46-3

Weight fraction :  $\geq 1 - < 5$  %  
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Eye Irrit. 2 ; H319

Oxirane, methyl-, polymer with oxirane, mono(2-propylheptyl) ether ; REACH No. : Polymer ; EC No. : 605-450-7; CAS No. : 166736-08-9

Weight fraction :  $\geq 1 - < 3$  %  
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302

QUATERNARY AMMONIA COMPOUNDS ; REACH No. : Polymer ; CAS No. : 863679-20-3

Weight fraction :  $\geq 1 - < 3$  %  
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Skin Irrit. 2 ; H315

DISODIUM METASILICATE ; REACH No. : 01-2119449811-37-XXXX ; EC No. : 229-912-9; CAS No. : 6834-92-0

Weight fraction :  $\geq 1 - < 3$  %  
Classification 1272/2008 [CLP] : Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 STOT SE 3 ; H335

#### Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

#### Following inhalation

In case of respiratory tract irritation, consult a physician.

#### In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Rub greasy ointment into the skin.

#### After eye contact

Protect uninjured eye. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

#### Following ingestion

Rinse mouth thoroughly with water. Let 1 glass of water be drunken in little sips (dilution effect). Do NOT induce vomiting. Call a physician immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. Causes skin irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water Foam Extinguishing powder Carbon dioxide (CO<sub>2</sub>) Sand Nitrogen Extinguishing blanket

#### Unsuitable extinguishing media

Full water jet

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

In case of fire may be liberated: Carbon monoxide , Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

### 5.4 Additional information

The product itself does not burn. Co-ordinate fire-fighting measures to the fire surroundings. Move undamaged containers from immediate hazard area if it can be done safely.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Special danger of slipping by leaking/spilling product. Use personal protection equipment.

### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### 6.3 Methods and material for containment and cleaning up

Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Wash with plenty of water. Treat the recovered material as prescribed in the section on waste disposal.

### 6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Keep container tightly closed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep/Store only in original container. Protect against : Frost .

#### Hints on joint storage

Storage class (TRGS 510) : 12

### 7.3 Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

BENZYL ALCOHOL ; CAS No. : 100-51-6

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 5 ppm / 22 mg/m<sup>3</sup>

Peak limitation : 2(l)

Remark : H, Y

Version : 23.06.2022

2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 10 ppm / 67 mg/m<sup>3</sup>

Peak limitation : 1,5(l)

Remark : Y

Version : 23.06.2022

Limit value type (country of origin) : STEL ( EC )

Limit value : 15 ppm / 101,2 mg/m<sup>3</sup>

Version : 20.06.2019

Limit value type (country of origin) : TWA ( EC )

Limit value : 10 ppm / 67,5 mg/m<sup>3</sup>

Version : 20.06.2019

#### DNEL-/PNEC-values

##### DNEL/DMEL

BENZYL ALCOHOL ; CAS No. : 100-51-6

Limit value type : DNEL Consumer (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 5,4 mg/m<sup>3</sup>

Limit value type : DNEL Consumer (systemic)

Exposure route : Inhalation

Exposure frequency : Short-term

Limit value : 27 mg/m<sup>3</sup>

Limit value type : DNEL Consumer (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 4 mg/kg bw/day

Limit value type : DNEL Consumer (systemic)

Exposure route : Dermal

Exposure frequency : Short-term

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

---

Limit value : 20 mg/kg bw/day  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : 4 mg/kg bw/day  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Oral  
Exposure frequency : Short-term  
Limit value : 20 mg/kg bw/day  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 22 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 110 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 8 mg/kg bw/day  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Short-term  
Limit value : 40 mg/kg bw/day  
2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : 6,25 mg/kg bw/day  
Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 67,5 mg/m<sup>3</sup>  
Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 101,2 mg/m<sup>3</sup>  
POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1  
Limit value type : DNEL Consumer (local)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 0,048 mg/cm<sup>2</sup>  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 6,6 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 68,1 mg/kg bw/day  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : 3,8 mg/kg bw/day  
Limit value type : DNEL worker (local)

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 0,096 mg/cm<sup>2</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 37,4 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 191 mg/kg bw/day  
SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5  
Limit value type : DNEL Consumer (local)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 0,048 mg/cm<sup>2</sup>  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 6,6 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 68,1 mg/kg bw/day  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : 3,8 mg/kg bw/day  
Limit value type : DNEL worker (local)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 0,096 mg/cm<sup>2</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 37,4 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 191 mg/kg bw/day  
ISOTRIDECANOL, ETHOXYLATED (>= 2.5) ; CAS No. : 9043-30-5  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 294 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 2080 mg/kg  
C9-C11, ALKOHOLS, ETHOXYLATED (4 EO) ; CAS No. : 68439-46-3  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 294 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

Exposure frequency : Long-term  
Limit value : 2080 mg/kg  
ALCOHOLS, ETHOXYLATED, C9-C11 (5.5 EO) ; CAS No. : 68439-46-3  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 294 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 2080 mg/kg  
DISODIUM METASILICATE ; CAS No. : 6834-92-0  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 1,55 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 0,74 mg/kg bw/day  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : 0,74 mg/kg bw/day  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 6,22 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 1,49 mg/kg

## PNEC

BENZYL ALCOHOL ; CAS No. : 100-51-6  
Limit value type : PNEC (Aquatic, freshwater)  
Limit value : 1 - 1,02 mg/l  
Limit value type : PNEC (Aquatic, intermittent release)  
Limit value : 2,3 mg/l  
Limit value type : PNEC (Aquatic, marine water)  
Limit value : 0,1 - 0,102 mg/l  
Limit value type : PNEC (Sediment, freshwater)  
Limit value : 5,27 mg/kg dw  
Limit value type : PNEC (Sediment, marine water)  
Limit value : 0,527 mg/kg dw  
Limit value type : PNEC (Soil)  
Limit value : 0,456 mg/kg dw  
Limit value type : PNEC (Sewage treatment plant)  
Limit value : 39 mg/l  
2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5  
Limit value type : PNEC (Aquatic, freshwater)  
Limit value : 1,1 mg/l  
Limit value type : PNEC (Aquatic, intermittent release)  
Limit value : 11 mg/l  
Limit value type : PNEC (Aquatic, marine water)  
Limit value : 0,11 mg/l  
Limit value type : PNEC (Sediment, freshwater)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

Limit value :	4,4 mg/kg dw
Limit value type :	PNEC (Sediment, marine water)
Limit value :	0,44 mg/kg dw
Limit value type :	PNEC (Soil)
Limit value :	0,32 mg/kg dw
Limit value type :	PNEC (Secondary poisoning)
Limit value :	56 mg/kg food
POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1	
Limit value type :	PNEC (Aquatic, freshwater)
Limit value :	0,1 mg/l
Limit value type :	PNEC (Aquatic, intermittent release)
Limit value :	1 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Limit value :	0,01 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Limit value :	0,372 mg/kg dw
Limit value type :	PNEC (Sediment, marine water)
Limit value :	0,0372 mg/l
Limit value type :	PNEC (Soil)
Limit value :	0,016 mg/kg dw
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	100 mg/l
SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5	
Limit value type :	PNEC (Aquatic, freshwater)
Limit value :	0,1 mg/l
Limit value type :	PNEC (Aquatic, intermittent release)
Limit value :	1 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Limit value :	0,01 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Limit value :	0,372 mg/kg dw
Limit value type :	PNEC (Sediment, marine water)
Limit value :	0,0372 mg/kg dw
Limit value type :	PNEC (Soil)
Limit value :	0,016 mg/kg dw
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	100 mg/l
DISODIUM METASILICATE ; CAS No. : 6834-92-0	
Limit value type :	PNEC (Aquatic, freshwater)
Limit value :	7,5 mg/l
Limit value type :	PNEC (Aquatic, intermittent release)
Limit value :	7,5 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Limit value :	1 mg/l
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	1000 mg/l

## 8.2 Exposure controls

### Personal protection equipment

#### Eye/face protection



Wear suitable safety goggles in case of splash.

**Suitable eye protection**

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

EN 166.

## Skin protection

### Hand protection



**Suitable gloves type** : EN 374.  
**Suitable material** : NBR (Nitrile rubber)  
**Breakthrough time** : 480 min.  
**Thickness of the glove material** : 0.4 mm

**Remark** : The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

## Respiratory protection



Respiratory protection necessary at: exceeding exposure limit values

### Suitable respiratory protection apparatus

Combination filtering device  
Type : A

### Remark

Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m<sup>3</sup> (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m<sup>3</sup> (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m<sup>3</sup> (1.0 % by vol.)  
Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

## General information

Do not put any product-impregnated cleaning rags into your trouser pockets. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. P362+P364 - Take off contaminated clothing and wash it before reuse. P264 - Wash hands thoroughly after handling.

## 8.3 Additional information

No tests have been performed. Selection made for preparations according to the best available knowledge and information on ingredients. In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid

**Colour** : colourless

#### Odour

flowery , spicy

#### Safety characteristics

**Freezing point** : <= -9 °C

**Initial boiling point and boiling range** : ( 1013 hPa ) approx. 100 °C

**Flash point** : not relevant

**Auto-ignition temperature** : ( 2-(2- 210 °C

DIN EN ISO 13736  
Literature value

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

	BUTOXYETHOXY)ETHANOL )			
Flammability :		non-flammable		
Lower explosion limit :	( 2-(2- BUTOXYETHOXY)ETHANOL )	0,7	Vol-%	Literature value
Upper explosion limit :	( BENZYL ALCOHOL )	13	Vol-%	Literature value
Vapour pressure :	( 20 °C )	<	24	hPa Calculated
Density :	( 20 °C )	approx.	1,03	g/cm <sup>3</sup>
Water solubility :	( 20 °C )		completely miscible	
pH :	( 20 °C )	approx.	13	
Cinematic viscosity :	( 20 °C )	<	30	mm <sup>2</sup> /s
Relative vapour density :	( 20 °C )		not determined	
Maximum VOC content (EC) :			0	Weight-%
Maximum VOC content (Switzerland) :			20,5	Weight-%
Taxable VOC content (Switzerland) :			20,5	Weight-%

## 9.2 Other information

No further relevant information available.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is considered to be non-reactive under normal use conditions.

### 10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

### 10.3 Possibility of hazardous reactions

Explosion hazard with: Phosphorus trichloride

Decomposition with: sulphuric acid . Decomposition takes place from temperatures above: 180 °C

### 10.4 Conditions to avoid

Avoid high temperatures or direct sunlight.

### 10.5 Incompatible materials

Brass , Zinc , Aluminium , Hydrogen bromide (HBr) , Oxidizing agent , sulphuric acid

### 10.6 Hazardous decomposition products

No known hazardous decomposition products.

Decomposition products in case of fire: see section 5.

### 10.7 Additional information

Slowly corrodes aluminium and zinc under hydrogen evolution.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Acute oral toxicity

Parameter :	ATEmix
Exposure route :	Oral
Effective dose :	> 2000 mg/kg
Parameter :	ATE ( Oxirane, methyl-, polymer with oxirane, mono(2-propylheptyl) ether ; CAS No. : 166736-08-9 )
Exposure route :	Oral
Effective dose :	500 mg/kg
Parameter :	LD50 ( QUATERNARY AMMONIA COMPOUNDS ; CAS No. : 863679-20-3 )
Exposure route :	Oral

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

Species : Rat  
Effective dose : > 300 mg/kg  
Parameter : LD50 ( DISODIUM METASILICATE ; CAS No. : 6834-92-0 )  
Exposure route : Oral  
Species : Mouse  
Effective dose : 770 - 820 mg/kg  
Parameter : LD50 ( POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1 )  
Exposure route : Oral  
Species : Rat  
Effective dose : > 7000 mg/kg  
Method : OECD 401  
Parameter : LD50 ( SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5 )  
Exposure route : Oral  
Species : Rat  
Effective dose : > 7000 mg/kg  
Method : OECD 401  
Parameter : LD50 ( C9-C11, ALKOHOLS, ETHOXYLATED (4 EO) ; CAS No. : 68439-46-3 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 5050 - 5130 mg/kg  
Method : OECD 401  
Parameter : LD50 ( ALCOHOLS, ETHOXYLATED, C9-C11 (5.5 EO) ; CAS No. : 68439-46-3 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 300 - 2000 mg/kg  
Method : OECD 401  
Parameter : LD50 ( DISODIUM METASILICATE ; CAS No. : 6834-92-0 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 1152 - 1349 mg/kg  
Parameter : LD50 ( 2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5 )  
Exposure route : Oral  
Species : Mouse  
Effective dose : 5530 mg/kg  
Method : OECD 401  
Parameter : LD50 ( ISOTRIDECANOL, ETHOXYLATED ( >= 2.5 ) ; CAS No. : 9043-30-5 )  
Exposure route : Oral  
Species : Rat  
Effective dose : > 2000 mg/kg  
Method : OECD 423  
Parameter : LD50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 1200 mg/kg

## Acute dermal toxicity

Parameter : ATEmix  
Exposure route : Dermal  
Effective dose : > 2000 mg/kg  
Parameter : LD50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : > 2000 mg/kg  
Parameter : LD50 ( POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : > 2000 mg/kg

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

Method : OECD 402  
Parameter : LD50 ( SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : > 2000 mg/kg  
Method : OECD 402  
Parameter : LD50 ( C9-C11, ALKOHOLS, ETHOXYLATED (4 EO) ; CAS No. : 68439-46-3 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : > 2000 mg/l  
Method : OECD 402  
Parameter : LD50 ( ALCOHOLS, ETHOXYLATED, C9-C11 (5.5 EO) ; CAS No. : 68439-46-3 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : > 2000 mg/kg  
Method : OECD 402  
Parameter : LD50 ( DISODIUM METASILICATE ; CAS No. : 6834-92-0 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : > 5000 mg/kg  
Parameter : LD50 ( ISOTRIDECANOL, ETHOXYLATED ( >= 2.5) ; CAS No. : 9043-30-5 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : > 2000 mg/kg  
Method : OECD 402  
Parameter : LD50 ( 2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 2764 mg/kg  
Method : OECD 402

### Acute inhalation toxicity

Parameter : ATEmix  
Exposure route : Inhalation  
Effective dose : > 20 mg/l  
Parameter : LC50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : > 4178 mg/m<sup>3</sup>  
Exposure time : 4 h  
Method : OECD 403  
Parameter : LC50 ( DISODIUM METASILICATE ; CAS No. : 6834-92-0 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : > 2,06 mg/l  
Exposure time : 4 h  
Parameter : LC50 ( POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : > 6,41 mg/l  
Exposure time : 232 min  
Method : OECD 403  
Parameter : LC50 ( SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : > 6,41 mg/l  
Exposure time : 232 min

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

Method : OECD 403  
Parameter : LC50 ( C9-C11, ALKOHOLS, ETHOXYLATED (4 EO) ; CAS No. : 68439-46-3 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : > 1,6 mg/l  
Method : OECD 403

## Corrosion

### Skin corrosion/irritation

Parameter : Skin corrosion/irritation ( DISODIUM METASILICATE ; CAS No. : 6834-92-0 )  
Species : Rabbit  
Result : Causes burns  
Method : OECD 404

### Assessment/classification

Causes skin irritation.

### Acid/alkaline reserve

The mixture has a low buffer capacity (Acid/Alkaline reserve).

### Serious eye damage/eye irritation

Parameter : Serious eye damage/eye irritation ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Albino rabbit  
Result : Causes serious eye irritation  
Method : OECD 405  
Parameter : Serious eye damage/eye irritation ( 2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5 )  
Species : Rabbit  
Result : Causes serious eye irritation  
Parameter : Serious eye damage/eye irritation ( POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1 )  
Species : Rabbit  
Result : Causes serious eye irritation  
Method : OECD 405  
Parameter : Serious eye damage/eye irritation ( SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5 )  
Species : Rabbit  
Result : Causes serious eye irritation  
Method : OECD 405  
Parameter : Serious eye damage/eye irritation ( DISODIUM METASILICATE ; CAS No. : 6834-92-0 )  
Result : Causes serious eye damage

### Assessment/classification

Causes serious eye damage.

## Respiratory or skin sensitisation

### Skin sensitisation

Parameter : Skin sensitisation ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Result : Other skin sensitiser (Subcategory 1B).  
Parameter : Skin sensitisation ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Result : contact allergen according to (EC) No. 1223/2009

### Assessment/classification

May cause an allergic skin reaction.

### Sensitisation to the respiratory tract

No further relevant information available.

### Assessment/classification

Based on available data, the classification criteria are not met.

Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

### Carcinogenicity

No further relevant information available.

### Germ cell mutagenicity

No further relevant information available.

### Reproductive toxicity

No further relevant information available.

## STOT-single exposure

No further relevant information available.

## STOT-repeated exposure

No further relevant information available.

## Aspiration hazard

No further relevant information available.

## 11.2 Information on other hazards

### Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

### Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

### Other adverse effects

May be absorbed through the skin. Frequently or prolonged contact with skin may cause dermal irritation. Has degreasing effect on the skin.

### Additional information

Preparation not tested. The statement is derived from the properties of the single components.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

Parameter :	LC50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )
Species :	Pimephales promelas (fathead minnow)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	460 mg/l
Exposure time :	96 h
Parameter :	LC50 ( 2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5 )
Species :	Lepomis macrochirus (Bluegill)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	1300 mg/l
Exposure time :	96 h
Method :	OECD 203
Parameter :	LC50 ( DISODIUM METASILICATE ; CAS No. : 6834-92-0 )
Species :	Fish
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	2320 mg/l
Exposure time :	96 h
Parameter :	LC50 ( POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1 )
Species :	Cyprinus carpio (Common Carp)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	> 100 mg/l
Exposure time :	96 h
Parameter :	LC50 ( SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5 )

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

Species : Cyprinus carpio (Common Carp)  
Evaluation parameter : Acute (short-term) fish toxicity  
Effective dose : > 100 mg/kg  
Exposure time : 96 h  
Parameter : LC50 ( ISOTRIDECANOL, ETHOXYLATED ( >= 2.5) ; CAS No. : 9043-30-5 )  
Species : Cyprinus carpio (Common Carp)  
Evaluation parameter : Acute (short-term) fish toxicity  
Effective dose : 1 - 10 mg/l  
Exposure time : 96 h  
Method : OECD 203  
Parameter : LC50 ( C9-C11, ALKOHOLS, ETHOXYLATED (4 EO) ; CAS No. : 68439-46-3 )  
Species : Oncorhynchus mykiss (Rainbow trout)  
Evaluation parameter : Acute (short-term) fish toxicity  
Effective dose : 5 - 7 mg/l  
Exposure time : 96 h  
Parameter : LC50 ( ALCOHOLS, ETHOXYLATED, C9-C11 (5.5 EO) ; CAS No. : 68439-46-3 )  
Species : Oncorhynchus mykiss (Rainbow trout)  
Evaluation parameter : Acute (short-term) fish toxicity  
Effective dose : 5 - 7 mg/l  
Exposure time : 96 h

**Chronic (long-term) fish toxicity**

Parameter : NOEC ( C9-C11, ALKOHOLS, ETHOXYLATED (4 EO) ; CAS No. : 68439-46-3 )  
Species : Pimephales promelas (fathead minnow)  
Evaluation parameter : Chronic (long-term) fish toxicity  
Effective dose : 0,11 - 0,28 mg/l  
Exposure time : 30 D  
Parameter : NOEC ( ALCOHOLS, ETHOXYLATED, C9-C11 (5.5 EO) ; CAS No. : 68439-46-3 )  
Species : Pimephales promelas (fathead minnow)  
Evaluation parameter : Chronic (long-term) fish toxicity  
Effective dose : 0,11 - 0,28 mg/l  
Exposure time : 30 D

**Acute (short-term) toxicity to crustacea**

Parameter : EC50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Acute (short-term) toxicity to crustacea  
Effective dose : 230 mg/ml  
Exposure time : 48 h  
Method : OECD 202  
Parameter : EC50 ( DISODIUM METASILICATE ; CAS No. : 6834-92-0 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Acute (short-term) toxicity to crustacea  
Effective dose : 1700 mg/l  
Exposure time : 48 h  
Method : OECD 202  
Parameter : EC50 ( SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Acute (short-term) toxicity to crustacea  
Effective dose : > 100 mg/l  
Exposure time : 48 h  
Parameter : EC50 ( C9-C11, ALKOHOLS, ETHOXYLATED (4 EO) ; CAS No. : 68439-46-3 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Acute (short-term) daphnia toxicity  
Effective dose : 2,5 mg/l  
Exposure time : 48 h  
Parameter : EC50 ( ALCOHOLS, ETHOXYLATED, C9-C11 (5.5 EO) ; CAS No. : 68439-46-3 )  
Species : Daphnia magna (Big water flea)

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

Evaluation parameter : Acute (short-term) daphnia toxicity  
Effective dose : 2,5 mg/l  
Exposure time : 48 h  
Parameter : EC50 ( ISOTRIDEKANOL, ETHOXYLATED ( >= 2.5 ) ; CAS No. : 9043-30-5 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Acute (short-term) toxicity to crustacea  
Effective dose : 1 - 10 mg/l  
Exposure time : 48 h  
Method : OECD 202  
Parameter : EC50 ( POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Acute (short-term) toxicity to crustacea  
Effective dose : > 100 mg/l  
Exposure time : 48 h  
Parameter : EC50 ( 2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Acute (short-term) toxicity to crustacea  
Effective dose : > 100 mg/l  
Exposure time : 48 h  
Method : OECD 202

**Chronic (long-term) toxicity to aquatic invertebrate**  
Parameter : NOEC ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Chronic (long-term) toxicity to aquatic invertebrate  
Effective dose : 51 mg/l  
Exposure time : 21 D  
Method : OECD 211  
Parameter : NOEC ( C9-C11, ALKOHOLS, ETHOXYLATED (4 EO) ; CAS No. : 68439-46-3 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Chronic (long-term) daphnia toxicity  
Effective dose : 0,77 - 1,75 mg/l  
Exposure time : 21 D  
Parameter : NOEC ( ALCOHOLS, ETHOXYLATED, C9-C11 (5.5 EO) ; CAS No. : 68439-46-3 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Chronic (long-term) daphnia toxicity  
Effective dose : 0,77 - 1,75 mg/l  
Exposure time : 21 D  
Parameter : NOEC ( ISOTRIDEKANOL, ETHOXYLATED ( >= 2.5 ) ; CAS No. : 9043-30-5 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Chronic (long-term) toxicity to aquatic invertebrate  
Effective dose : 0,37 mg/l  
Exposure time : 21 D

**Acute (short-term) toxicity to algae and cyanobacteria**  
Parameter : EC50 ( DISODIUM METASILICATE ; CAS No. : 6834-92-0 )  
Species : Scenedesmus subspicatus  
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria  
Effective dose : 207 mg/l  
Exposure time : 72 h  
Method : DIN 38412 / part 9  
Parameter : EC50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Pseudokirchneriella subcapitata  
Evaluation parameter : Inhibition of growth rate  
Effective dose : 770 mg/l  
Exposure time : 72 h  
Method : OECD 201  
Parameter : EC50 ( C9-C11, ALKOHOLS, ETHOXYLATED (4 EO) ; CAS No. : 68439-46-3 )

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

Species : Pseudokirchneriella subcapitata  
Evaluation parameter : Acute (short-term) algae toxicity  
Effective dose : 1,4 mg/l  
Exposure time : 96 h  
Parameter : EC50 ( ALCOHOLS, ETHOXYLATED, C9-C11 (5.5 EO) ; CAS No. : 68439-46-3 )  
Species : Pseudokirchneriella subcapitata  
Evaluation parameter : Acute (short-term) algae toxicity  
Effective dose : 1,4 mg/l  
Exposure time : 96 h  
Parameter : EC50 ( 2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5 )  
Species : Scenedesmus subspicatus  
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria  
Effective dose : > 100 mg/l  
Exposure time : 48 h  
Method : OECD 201  
Parameter : EC50 ( POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1 )  
Species : Desmodesmus subspicatus  
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria  
Effective dose : > 100 mg/l  
Exposure time : 72 h  
Parameter : EC50 ( SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5 )  
Species : Desmodesmus subspicatus  
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria  
Effective dose : > 100 mg/l  
Exposure time : 72 h  
Parameter : EC50 ( ISOTRIDEKANOL, ETHOXYLATED ( >= 2.5) ; CAS No. : 9043-30-5 )  
Species : Desmodesmus subspicatus  
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria  
Effective dose : 1 - 10 mg/l  
Exposure time : 72 h  
Method : OECD 201

**Toxicity to microorganisms**

Parameter : EC50 ( DISODIUM METASILICATE ; CAS No. : 6834-92-0 )  
Species : Toxicity to microorganisms  
Effective dose : > 100 mg/l  
Exposure time : 3 h  
Parameter : EC50 ( POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1 )  
Species : Toxicity to microorganisms  
Effective dose : > 1000 mg/l  
Exposure time : 3 h  
Parameter : EC50 ( SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5 )  
Species : Toxicity to microorganisms  
Effective dose : > 1000 mg/l  
Parameter : EC50 ( ISOTRIDEKANOL, ETHOXYLATED ( >= 2.5) ; CAS No. : 9043-30-5 )  
Species : Bacteria toxicity  
Effective dose : 140 mg/l  
Parameter : EC50 ( C9-C11, ALKOHOLS, ETHOXYLATED (4 EO) ; CAS No. : 68439-46-3 )  
Species : Pseudomonas putida  
Evaluation parameter : Bacteria toxicity  
Effective dose : > 10 g/l  
Exposure time : 16,9 h  
Method : DIN 38412 / part 8  
Parameter : EC50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Toxicity to microorganisms  
Effective dose : 2100 mg/l  
Exposure time : 49 h

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

Parameter : EC50 ( ALCOHOLS, ETHOXYLATED, C9-C11 (5.5 EO) ; CAS No. : 68439-46-3 )  
Species : Pseudomonas putida  
Evaluation parameter : Bacteria toxicity  
Effective dose : > 10 g/l  
Exposure time : 16,9 h  
Method : DIN 38412 / part 8  
Parameter : EC10 ( ALCOHOLS, ETHOXYLATED, C9-C11 (5.5 EO) ; CAS No. : 68439-46-3 )  
Species : Pseudomonas putida  
Evaluation parameter : Bacteria toxicity  
Effective dose : > 10 g/l  
Exposure time : 16,9 h  
Method : DIN 38412 / part 8  
Parameter : EC10 ( 2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5 )  
Species : Toxicity to microorganisms  
Effective dose : > 1995 mg/l  
Exposure time : 30 min  
Parameter : EC10 ( C9-C11, ALKOHOLS, ETHOXYLATED (4 EO) ; CAS No. : 68439-46-3 )  
Species : Pseudomonas putida  
Evaluation parameter : Bacteria toxicity  
Effective dose : > 10 g/l  
Exposure time : 16,9 h  
Method : DIN 38412 / part 8

## Terrestrial toxicity

### Toxicity to soil macroorganisms except of arthropods

#### Chronical earthworm toxicity (reproduction)

Parameter : NOEC ( ISOTRIDECANOL, ETHOXYLATED ( >= 2.5) ; CAS No. : 9043-30-5 )  
Species : Eisenia fetida  
Evaluation parameter : Chronical earthworm toxicity (reproduction)  
Effective dose : 220 mg/kg

## 12.2 Persistence and degradability

### Biodegradation

Parameter : Biodegradation ( POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1 )  
Inoculum : Biodegradation  
Evaluation parameter : Aerobic  
Degradation rate : 99,8 %  
Test duration : 28 D  
Evaluation : Readily biodegradable (according to OECD criteria).  
Method : OECD 301B  
Parameter : Biodegradation ( SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5 )  
Inoculum : Biodegradation  
Evaluation parameter : Aerobic  
Degradation rate : 99,8 %  
Test duration : 28 D  
Evaluation : Readily biodegradable (according to OECD criteria).  
Method : OECD 301B  
Parameter : Biodegradation ( C9-C11, ALKOHOLS, ETHOXYLATED (4 EO) ; CAS No. : 68439-46-3 )  
Inoculum : Biodegradation  
Evaluation parameter : Aerobic  
Degradation rate : 72 %  
Test duration : 28 D  
Evaluation : Readily biodegradable (according to OECD criteria).  
Parameter : Biodegradation ( ALCOHOLS, ETHOXYLATED, C9-C11 (5.5 EO) ; CAS No. : 68439-46-3 )  
Inoculum : Biodegradation

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

Degradation rate : > 60 %  
Evaluation : Readily biodegradable (according to OECD criteria).  
Method : OECD 301B  
Parameter : Biodegradation ( Oxirane, methyl-, polymer with oxirane, mono(2-propylheptyl) ether ; CAS No. : 166736-08-9 )  
Inoculum : Biodegradation  
Degradation rate : > 60 %  
Test duration : 28 D  
Evaluation : Readily biodegradable (according to OECD criteria).  
Method : OECD 301B  
Parameter : Biodegradation ( QUATERNARY AMMONIA COMPOUNDS ; CAS No. : 863679-20-3 )  
Inoculum : Biodegradation  
Degradation rate : > 60 %  
Test duration : 28 D  
Evaluation : Readily biodegradable (according to OECD criteria).  
Method : OECD 301D  
Parameter : Biodegradation ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Inoculum : Biodegradation  
Degradation rate : 95 - 97 %  
Test duration : 21 D  
Evaluation : Readily biodegradable (according to OECD criteria).  
Method : OECD 301A  
Parameter : BOD (% of COD) ( 2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5 )  
Inoculum : Biodegradation  
Evaluation parameter : Aerobic  
Degradation rate : 95 %  
Test duration : 28 D  
Evaluation : Readily biodegradable (according to OECD criteria).  
Method : OECD 301C  
Parameter : CO2 formation (% of the theoretical value) ( ISOTRIDEKANOL, ETHOXYLATED ( >= 2.5) ; CAS No. : 9043-30-5 )  
Inoculum : Biodegradation  
Evaluation parameter : Aerobic  
Degradation rate : > 60 %  
Test duration : 28 D  
Evaluation : Readily biodegradable (according to OECD criteria).  
Method : OECD 301B  
Parameter : CO2 formation (% of the theoretical value) ( ISOTRIDEKANOL, ETHOXYLATED ( >= 2.5) ; CAS No. : 9043-30-5 )  
Inoculum : Degree of elimination  
Evaluation parameter : Anaerobic  
Degradation rate : > 60 %  
Test duration : 60 D  
Evaluation : Biodegradable.  
Method : OECD 311

## 12.3 Bioaccumulative potential

Parameter : Partition coefficient n-octanol/water (log value) ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Value : 1,05  
20 °C  
Parameter : Partition coefficient n-octanol/water (log value) ( 2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5 )  
Value : 1  
20 °C  
Method : OECD 117  
No indication of bioaccumulation potential.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

## 12.4 Mobility in soil

No information available.

## 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7 Other adverse effects

No information available.

## 12.8 Additional ecotoxicological information

P273 - Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Directive 2008/98/EC (Waste Framework Directive)

##### Before intended use

##### Waste codes/waste designations according to EWC/AVV

07 06 01\* (Aqueous washing liquids and mother liquors)

20 01 29\* (Detergents containing hazardous substances)

##### Other disposal recommendations

Dispose of waste according to applicable legislation. Dispose of contents/container to an appropriate recycling or disposal facility. Contaminated packages must be completely emptied and can be re-used following proper cleaning (Water (with cleaning agent)). Handle contaminated packages in the same way as the substance itself.

### 13.2 Additional information

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

## SECTION 14: Transport information

### 14.1 UN number or ID number

No dangerous good in sense of these transport regulations.

### 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

### 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

### 14.4 Packing group

No dangerous good in sense of these transport regulations.

### 14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

### 14.6 Special precautions for user

None

### 14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

## Authorisations and/or restrictions on use

### Restrictions on use

Use restriction according to REACH annex XVII, no. : 3, 55, 75

### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

### Other regulations (EU)

#### Labelling for contents according to regulation (EC) No. 648/2004

5 - 15 % non-ionic surfactants

5 - 15 % anionic surfactants

< 5 % cationic surfactants

Contains the following substances: Benzyl Alcohol

### National regulations

#### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

#### Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

## 15.2 Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

## SECTION 16: Other information

### 16.1 Indication of changes

02. Classification of the substance or mixture · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 08. DNEL/DMEL · 08. PNEC · 09. Information on basic physical and chemical properties · 11. Information on toxicological effects · 12. Bioaccumulative potential

### 16.2 Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (Europäisches Übereinkommen über die Beförderung gefährlicher Güter auf der Straße)  
AOX: adsorbierbare organisch gebundene Halogene  
AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen  
CAS: Chemical Abstracts Service (Unterabteilung der American Chemical Society)  
CLP: Verordnung (EG) Nr. 1272/2008 über die Einstufung, Kennzeichnung und Verpackung von Stoffen und Gemischen (Classification Labelling and Packaging)  
EAK / AVV: europäischer Abfallartenkatalog / Abfallverzeichnis-Verordnung  
ECHA: Europäische Chemikalienagentur (European Chemicals Agency)  
EINECS: : Altstoffverzeichnis (European Inventory of Existing Commercial Chemical Substances)  
GHS: Global harmonisiertes System zur Einstufung und Kennzeichnung von Chemikalien (Globally Harmonized System of Classification and Labelling of Chemicals)  
IATA: Internationale Luftverkehrs-Vereinigung (International Air Transport Association)  
ICAO: Internationale Zivilluftfahrtorganisation (International Civil Aviation Organization)  
IMDG: Gefahrgutkennzeichnung für gefährliche Güter im Seeschiffverkehr (International Maritime Code for Dangerous Goods)  
RID: Regelung zur internationalen Beförderung gefährlicher Güter im Schienenverkehr (Règlement concernant le transport international ferroviaire de marchandises dangereuses)  
TRGS: Technische Regel für den Umgang mit Gefahrstoffen  
VbF: Verordnung über brennbare Flüssigkeiten  
VOC: flüchtige organische Verbindung (volatile organic compound)  
VVEA: Verordnung über die Vermeidung und die Entsorgung von Abfällen  
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe  
WGK: Wassergefährdungsklasse

### 16.3 Key literature references and sources for data

DGUV: GESTIS-Stoffdatenbank

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stripper  
Revision date : 22.07.2025  
Print date : 22.07.2025

Version (Revision) : 5.3.0 (5.2.1)

ECHA: Classification And Labelling Inventory  
ECHA: Pre-registered Substances  
ECHA: Registered Substances  
EC Safety Data Sheet of Suppliers  
ESIS: European Chemical Substances Information System  
GDL: Gefahrstoffdatenbank der Länder  
UBA Rigoletto: Wassergefährdende Stoffe  
Regulation (EC) No. 1907/2006 of the European Parliament and of the Council  
|-> COMMISSION REGULATION (EU) 2020/878 of 18 June 2020  
Regulation (EC) No. 1272/2008 of the European Parliament and of the Council

## 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Evaluation :

Skin Irrit. 2 : Calculation method.

Eye Dam. 1 : Calculation method.

## 16.5 Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

## 16.6 Training advice

None

## 16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.