

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 28.05.2020
Print date : 28.05.2020

Version (Revision) : 3.1.0 (3.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

PROLAQ L 500

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

PC 35 - Washing and cleaning products

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Bio-Circle Surface Technology GmbH

Street : Berensweg 200

Postal code/city : 33334 Gütersloh

Telephone : +49 5241 9443 0

Telefax : +49 5241 9443 44

Information contact : labor@bio-circle.de

1.4 Emergency telephone number

+49 5241 9443 51 during normal office hours

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Exclamation mark (GHS07)

Signal word

Warning

Hazard statements

H319 Causes serious eye irritation.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

2-(2-BUTOXYETHOXY)ETHANOL ; REACH No. : 01-2119475104-44-XXXX ; EC No. : 203-961-6; CAS No. : 112-34-5

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 28.05.2020
Print date : 28.05.2020

Version (Revision) : 3.1.0 (3.0.0)

Weight fraction : $\geq 10 - < 25 \%$
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319
Substance with a common (EC) occupational exposure limit value.

DIMETHYL SUCCINATE ; REACH No. : 01-2119486681-29-XXXX ; EC No. : 203-419-9; CAS No. : 106-65-0
Weight fraction : $\geq 10 - < 25 \%$
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

2-BUTOXYETHANOL ; REACH No. : 01-2119475108-36-XXXX ; EC No. : 203-905-0; CAS No. : 111-76-2
Weight fraction : $\geq 5 - < 10 \%$
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315
Eye Irrit. 2 ; H319
Substance with a common (EC) occupational exposure limit value.

N-BUTYL ACETATE ; EC No. : 204-658-1; CAS No. : 123-86-4
Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336

1-METHOXY-2-PROPANOL ; REACH No. : 01-2119457435-35-XXXX ; EC No. : 203-539-1; CAS No. : 107-98-2
Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336
Substance with a common (EC) occupational exposure limit value.

Further ingredients

DIMETHYL GLUTARATE ; EC No. : 214-277-2; CAS No. : 1119-40-0
Weight fraction : $\geq 30 - < 35 \%$

DIMETHYL ADIPATE ; EC No. : 211-020-6; CAS No. : 627-93-0
Weight fraction : $\geq 5 - < 10 \%$

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation

In case of respiratory tract irritation, consult a physician.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Rub greasy ointment into the skin.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Rinse mouth thoroughly with water. Let 1 glass of water be drunken in little sips (dilution effect). Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 28.05.2020
Print date : 28.05.2020

Version (Revision) : 3.1.0 (3.0.0)

Water Foam Extinguishing powder Carbon dioxide (CO₂) Sand Nitrogen Extinguishing blanket

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide , Carbon dioxide (CO₂)

5.3 Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Apply foam in abundant quantities since some of it gets destroyed by the product. Do not allow run-off from fire-fighting to enter drains or water courses. The product itself does not burn. Adapt extinguishing measures to suit the environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Special danger of slipping by leaking/spilling product.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3 Methods and material for containment and cleaning up

Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Wash with plenty of water. Treat the recovered material as prescribed in the section on waste disposal.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed.

7.2 Conditions for safe storage, including any incompatibilities

Keep/Store only in original container. Protect against Frost

Hints on joint storage

Storage class (TRGS 510) : 10

7.3 Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

DIMETHYL GLUTARATE ; CAS No. : 1119-40-0

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 1,2 ppm / 8 mg/m³

Peak limitation : 2(l)

Remark : Y

Version : 29.03.2019

2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 28.05.2020
Print date : 28.05.2020

Version (Revision) : 3.1.0 (3.0.0)

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 10 ppm / 67 mg/m³
Peak limitation : 1,5(l)
Remark : Y
Version : 29.03.2019

Limit value type (country of origin) : STEL (EC)
Limit value : 15 ppm / 101,2 mg/m³
Version : 20.06.2019

Limit value type (country of origin) : TWA (EC)
Limit value : 10 ppm / 67,5 mg/m³
Version : 20.06.2019

2-(2-BUTOXYETHOXY)ETHYL ACETATE ; CAS No. : 124-17-4
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 10 ppm / 67 mg/m³
Peak limitation : 1,5(l)
Remark : Y
Version : 29.03.2019

DIMETHYL SUCCINATE ; CAS No. : 106-65-0
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 1,2 ppm / 8 mg/m³
Peak limitation : 2(l)
Remark : Y
Version : 29.03.2019

DIMETHYL ADIPATE ; CAS No. : 627-93-0
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 1,2 ppm / 8 mg/m³
Peak limitation : 2(l)
Remark : Y
Version : 29.03.2019

2-BUTOXYETHANOL ; CAS No. : 111-76-2
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 10 ppm / 49 mg/m³
Peak limitation : 2(II)
Remark : H,Y
Version : 29.03.2019

Limit value type (country of origin) : STEL (EC)
Limit value : 50 ppm / 246 mg/m³
Remark : Skin
Version : 20.06.2019

Limit value type (country of origin) : TWA (EC)
Limit value : 20 ppm / 98 mg/m³
Remark : Skin
Version : 20.06.2019

N-BUTYL ACETATE ; CAS No. : 123-86-4
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 62 ppm / 300 mg/m³
Peak limitation : 2(l)
Remark : Y
Version : 29.03.2019

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 100 ppm / 370 mg/m³
Peak limitation : 2(l)
Remark : Y

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 28.05.2020
Print date : 28.05.2020

Version (Revision) : 3.1.0 (3.0.0)

Version : 29.03.2019
Limit value type (country of origin) : STEL (EC)
Limit value : 150 ppm / 568 mg/m³
Remark : Skin
Version : 20.06.2019
Limit value type (country of origin) : TWA (EC)
Limit value : 100 ppm / 375 mg/m³
Remark : Skin
Version : 20.06.2019

Biological limit values

2-BUTOXYETHANOL ; CAS No. : 111-76-2

Limit value type (country of origin) : TRGS 903 (D)
Parameter : Butoxy acetic acid / Urine (U) / At long term exposure: after several previous shifts
Limit value : 100 mg/l
Version : 29.03.2019

Limit value type (country of origin) : TRGS 903 (D)
Parameter : Butoxy acetic acid / Urine (U) / End of exposure or end of shift ; At long term exposure: after several previous shifts
Limit value : 150 mg/g Kr
Version : 29.03.2019

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

Limit value type (country of origin) : TRGS 903 (D)
Parameter : 1-methoxy-2-propanol / Urine (U) / End of exposure or end of shift
Limit value : 15 mg/l
Version : 29.03.2019

DNEL-/PNEC-values

DNEL/DMEL

Limit value type : DNEL worker (local) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 67,5 mg/m³

Limit value type : DNEL worker (local) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 101,2 mg/m³

Limit value type : DNEL worker (systemic) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 67,5 mg/m³

Limit value type : DNEL worker (systemic) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 20 mg/kg

Limit value type : DNEL worker (local) (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 246 mg/m³

Limit value type : DNEL worker (systemic) (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 98 mg/m³

Limit value type : DNEL worker (systemic) (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 663 mg/m³

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 28.05.2020
Print date : 28.05.2020

Version (Revision) : 3.1.0 (3.0.0)

Limit value type : DNEL worker (systemic) (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 75 mg/kg
Limit value type : DNEL worker (systemic) (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Dermal
Exposure frequency : Short-term
Limit value : 89 mg/kg
Limit value type : DNEL worker (local) (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 480 mg/m³
Limit value type : DNEL worker (local) (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 960 mg/m³
Limit value type : DNEL worker (systemic) (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 480 mg/m³
Limit value type : DNEL worker (systemic) (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 960 mg/m³
Limit value type : DNEL worker (local) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 553,5 mg/m³
Limit value type : DNEL worker (systemic) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 369 mg/m³
Limit value type : DNEL worker (systemic) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 50,6 mg/kg

PNEC

Limit value type : PNEC (Aquatic, freshwater) (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Limit value : 8,8 mg/l
Limit value type : PNEC (Aquatic, marine water) (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Limit value : 0,88 mg/l
Limit value type : PNEC (Sediment, freshwater) (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Limit value : 34,6 mg/kg
Limit value type : PNEC (Soil) (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Limit value : 2,33 mg/kg
Limit value type : PNEC (Sewage treatment plant) (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Limit value : 463 mg/l

8.2 Exposure controls

Personal protection equipment

Eye/face protection



Wear suitable safety goggles in case of splash.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 28.05.2020
Print date : 28.05.2020

Version (Revision) : 3.1.0 (3.0.0)

Suitable eye protection

EN 166.

Skin protection

Hand protection



Wear protective gloves in case of longer lasting skin contact.

Suitable gloves type : EN 374.

Suitable material : NBR (Nitrile rubber)

Breakthrough time (maximum wearing time) : 480 min.

Thickness of the glove material : 0.4 mm

Remark : The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Respiratory protection



Respiratory protection necessary at: exceeding exposure limit values

Suitable respiratory protection apparatus

Combination filtering device (EN 14387)

Type : A

Remark

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

General information

Do not put any product-impregnated cleaning rags into your trouser pockets. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. P362+P364 - Take off contaminated clothing and wash it before reuse. P264 - Wash hands thoroughly after handling.

8.3 Additional information

No tests have been performed. Selection made for preparations according to the best available knowledge and information on ingredients. In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid

Colour : colourless

Odour

characteristic

Safety characteristics

Initial boiling point and boiling range (1013 hPa)	>	100 °C
:		
Flash point :	approx.	61 °C
Auto-ignition temperature :		not determined
Vapour pressure :	(50 °C)	not determined
Density :	(20 °C)	1 g/cm ³

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 28.05.2020
Print date : 28.05.2020

Version (Revision) : 3.1.0 (3.0.0)

pH : not applicable
Maximum VOC content (EC) : < 20 Wt %
Maximum VOC content (Switzerland) : 32,5 Wt %
:

9.2 Other information

The sustaining combustion test for liquids was carried out (liquid does not sustain combustion). The result is negative.

SECTION 10: Stability and reactivity

10.1 Reactivity

Reactions with strong oxidants are expected. Peroxides can be produced.

10.2 Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

No known hazardous decomposition products.
Decomposition products in case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity

Parameter :	ATEmix calculated
Exposure route :	Oral
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route :	Oral
Species :	Mouse
Effective dose :	5530 mg/kg
Method :	OECD 401
Parameter :	LD50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route :	Oral
Species :	Rat
Effective dose :	14 g/kg
Parameter :	LD50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route :	Oral
Species :	Rabbit
Effective dose :	7,4 g/kg
Parameter :	LD50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route :	Oral
Species :	Rat
Effective dose :	1250 - 1490 mg/kg
Method :	OECD 401

Acute dermal toxicity

Parameter :	ATEmix calculated
Exposure route :	Dermal
Effective dose :	> 2000 mg/kg

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 28.05.2020
Print date : 28.05.2020

Version (Revision) : 3.1.0 (3.0.0)

Parameter : LD50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route : Dermal
Species : Rabbit
Effective dose : 2764 mg/kg
Method : OECD 402
Parameter : LD50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Dermal
Species : Rabbit
Effective dose : 841 mg/kg
Method : OECD 402

Acute inhalation toxicity

Parameter : ATEmix calculated
Exposure route : Inhalation
Effective dose : > 20 mg/l
Parameter : LC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route : Inhalation
Species : Rat
Effective dose : > 21 mg/l
Exposure time : 4 h
Method : OECD 403
Parameter : LC50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Inhalation
Species : Rat
Effective dose : 2 - 20 mg/l
Exposure time : 4 h

Corrosion

Skin corrosion/irritation

No further relevant information available.

Serious eye damage/eye irritation

No further relevant information available.

Respiratory or skin sensitisation

Skin sensitisation

No further relevant information available.

Sensitisation to the respiratory tract

No further relevant information available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

No further relevant information available.

Germ cell mutagenicity

No further relevant information available.

Reproductive toxicity

No further relevant information available.

STOT-single exposure

No further relevant information available.

STOT-repeated exposure

No further relevant information available.

Aspiration hazard

No further relevant information available.

11.2 Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

11.3 Other adverse effects

Frequently or prolonged contact with skin may cause dermal irritation. Has degreasing effect on the skin.

Trade name : PROLAQ L 500
Revision date : 28.05.2020
Print date : 28.05.2020

Version (Revision) : 3.1.0 (3.0.0)

11.4 Additional information

Preparation not tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter :	LC50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Species :	Lepomis macrochirus (Bluegill)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	1300 mg/l
Exposure time :	96 h
Method :	OECD 203
Parameter :	LC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species :	Pimephales promelas (fathead minnow)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	18 mg/l
Exposure time :	96 h
Method :	OECD 203
Parameter :	LC50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Species :	Oncorhynchus mykiss (Rainbow trout)
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	1474 mg/l
Exposure time :	96 h
Method :	OECD 203
Parameter :	LC50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Species :	Daphnia magna (Big water flea)
Evaluation parameter :	Acute (short-term) daphnia toxicity
Effective dose :	1815 mg/l
Exposure time :	24 h
Method :	DIN 38412 / part 11
Parameter :	LC50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Species :	Daphnia magna (Big water flea)
Evaluation parameter :	Chronic (long-term) daphnia toxicity
Effective dose :	297 mg/l
Exposure time :	21 D
Method :	OECD 211

Acute (short-term) toxicity to crustacea

Parameter :	EC50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Species :	Daphnia magna (Big water flea)
Evaluation parameter :	Acute (short-term) daphnia toxicity
Effective dose :	> 100 mg/l
Exposure time :	48 h
Method :	OECD 202

Chronic (long-term) toxicity to crustacea

Parameter :	NOEC (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species :	Daphnia magna (Big water flea)
Evaluation parameter :	Chronic (long-term) daphnia toxicity
Effective dose :	23 mg/l
Exposure time :	21 D
Method :	OECD 211
Parameter :	NOEC (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species :	Desmodesmus subspicatus
Evaluation parameter :	Acute (short-term) algae toxicity

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 28.05.2020
Print date : 28.05.2020

Version (Revision) : 3.1.0 (3.0.0)

Effective dose : 200 mg/l
Exposure time : 72 h
Parameter : NOEC (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Species : Brachydanio rerio (zebra-fish)
Evaluation parameter : Chronic (long-term) fish toxicity
Effective dose : > 100 mg/l
Exposure time : 21 D
Method : OECD 204
Parameter : NOEC (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Chronic (long-term) daphnia toxicity
Effective dose : 100 mg/l
Exposure time : 21 D
Method : OECD 211
Parameter : NOEC (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Species : Algae
Effective dose : 286 mg/l
Exposure time : 72 h
Method : OECD 201

Acute (short-term) toxicity to aquatic algae and cyanobacteria

Parameter : EC50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Species : Scenedesmus subspicatus
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : > 100 mg/l
Exposure time : 48 h
Method : OECD 201
Parameter : EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species : Pimephales promelas (fathead minnow)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : 18 mg/l
Exposure time : 96 h
Method : OECD 203
Parameter : EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species : Daphnia
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : 44 mg/l
Exposure time : 48 h
Parameter : EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Chronic (long-term) daphnia toxicity
Effective dose : 34 mg/l
Exposure time : 21 D
Method : OECD 211
Parameter : EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species : Desmodesmus subspicatus
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : 674,7 mg/l
Exposure time : 72 h
Parameter : EC50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Species : Algae
Effective dose : 1840 mg/l
Exposure time : 72 h
Method : OECD 201

Toxicity to microorganisms

Parameter : EC10 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Species : Bacteria toxicity

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 28.05.2020
Print date : 28.05.2020

Version (Revision) : 3.1.0 (3.0.0)

Effective dose : > 1995 mg/l
Exposure time : 30 min

12.2 Persistence and degradability

Biodegradation

Parameter : Biodegradation (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Inoculum : Biodegradation
Degradation rate : 90 - 100 %
Test duration : 14 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301E
Parameter : Biodegradation (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Inoculum : Biodegradation
Degradation rate : 90 - 100 %
Test duration : 8 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 302B
Parameter : Biodegradation (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : 83 %
Test duration : 20 D
Evaluation : Readily biodegradable (according to OECD criteria).
Parameter : Biodegradation (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Inoculum : Biodegradation
Degradation rate : 88 %
Test duration : 20 D

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. List of proposed waste codes/waste designations in accordance with EWC

13.1 Waste treatment methods

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

08 01 17 * - Waste from paint or varnish removal containing organic solvents or other dangerous substances.

Waste code packaging

15 01 02 - plastic packaging.

Waste treatment options

Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Handle contaminated packages in the same way as the substance itself.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 28.05.2020
Print date : 28.05.2020

Version (Revision) : 3.1.0 (3.0.0)

13.2 Additional information

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No transport as bulk according to IBC Code.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Use restriction according to REACH annex XVII, no. : 3, 40, 55

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

National regulations

AT: Labelling according to Austrian regulations (Chemikaliengesetz/ChemV).

CH: Chemikalienverordnung (ChemV) and Chemikalien-Risikoreduktions-Verordnung (Chem RRV) are complied.

Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : 5 - 10 %

Water hazard class (WGK)

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

15.2 Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

03. Hazardous ingredients · 11. Acute toxicity · 12. Toxicity · 12. Persistence and degradability

16.2 Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (Europäisches Übereinkommen über die Beförderung gefährlicher Güter auf der Straße)

AOX: adsorbierbare organisch gebundene Halogene

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L 500
Revision date : 28.05.2020
Print date : 28.05.2020

Version (Revision) : 3.1.0 (3.0.0)

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen
CAS: Chemical Abstracts Service (Unterabteilung der American Chemical Society)
CLP: Verordnung (EG) Nr. 1272/2008 über die Einstufung, Kennzeichnung und Verpackung von Stoffen und Gemischen (Classification Labelling and Packaging)
EAK / AVV: europäischer Abfallartenkatalog / Abfallverzeichnis-Verordnung
ECHA: Europäische Chemikalienagentur (European Chemicals Agency)
EINECS: : Altstoffverzeichnis (European Inventory of Existing Commercial Chemical Substances)
GHS: Global harmonisiertes System zur Einstufung und Kennzeichnung von Chemikalien (Globally Harmonized System of Classification and Labelling of Chemicals)
IATA: Internationale Luftverkehrs-Vereinigung (International Air Transport Association)
ICAO: Internationale Zivilluftfahrtorganisation (International Civil Aviation Organization)
IMDG: Gefahrgutkennzeichnung für gefährliche Güter im Seeschiffverkehr (International Maritime Code for Dangerous Goods)
RID: Regelung zur internationalen Beförderung gefährlicher Güter im Schienenverkehr (Règlement concernant le transport international ferroviaire de marchandises dangereuses)
TRGS: Technische Regel für den Umgang mit Gefahrstoffen
VbF: Verordnung über brennbare Flüssigkeiten
VOC: flüchtige organische Verbindung (volatile organic compound)
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe
WGK: Wassergefährdungsklasse

16.3 Key literature references and sources for data

DGUV: GESTIS-Stoffdatenbank
ECHA: Classification And Labelling Inventory
ECHA: Pre-registered Substances
ECHA: Registered Substances
EC_Safety Data Sheet of Suppliers
ESIS: European Chemical Substances Information System
GDL: Gefahrstoffdatenbank der Länder
UBA Rigoletto: Wassergefährdende Stoffe
Regulation (EC) No. 1907/2006 of the European Parliament and of the Council
Regulation (EC) No. 1272/2008 of the European Parliament and of the Council

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.