

Technical Datasheet



Trade name : Smoke Resin Remover
Reviewed: 22.10.2021
Date of print : 22.10.2021

Page : 1 of 1

Description

Smoke Resin Remover is a aqueous, highly concentrated, solvent- and phosphate-free intensive Cleaner with active foam. The cleaner removes most stubborn contaminants such as smoke gummy, gummy fats, oils and protein residue. Smoke Resin Remover is NSF-certified, category: A1; registration-No.: 147908

Chemical characterisation

Aqueous, alkaline, strongly foaming surfactant

Classification according to Regulation (EC) No.1272/2008 [CLP]

Eye Dam. 1; H318 - Serious eye damage/eye irritation: Category 1; Causes serious eye damage.
Skin Corr. 1A; H314 - Skin corrosion/irritation: Category 1A; Causes severe skin burns and eye damage.
Met. Corr. 1; H290 - Corrosive to metals: Category 1; May be corrosive to metals.

Transport information

ADR : UN 1760 CORROSIVE LIQUID, N.O.S. (POTASSIUM HYDROXIDE SOLUTION)

Water hazard class (Classification according to AwSV)

Water hazard class : 1 (Slightly hazardous to water)

Labelling for contents according to regulation (EC) No. 648/2004

< 5 % non-ionic surfactants

Safety equipment

Eye / Face protection:	suitable safety goggles acc. EN 166	In case of splash
Hand protection:	suitable gloves type EN 374	In case of possible skin contact
Respiratory protection:	Combination filtering device DIN EN 14387	In case of exceeding exposure limit values

Application

Universally throughout the food industry to remove stubborn stains and soilings used
- For cleaning smoke chambers, cookers, filters, fume cupboards, stoves, etc.
- Ideal for cleaning of flue deductions and in commercial kitchens, restaurant kitchens and canteens, deposits of vent pipes and burnt into the surface of grills, baking and pizza ovens
- Removes smoke resin deposits very well in smoking chambers
- To clean the air circulation system in smoking chambers

Advice: Do not apply concentrated on aluminium or zinc-plated surfaces

Technical data

Appearance :	liquid		
Colour :	transparent		
Odour :	odourless		
Boiling temperature :	ca. 95 °C	Solidifying temperature :	-2 °C
Flash point :	not applicable	Ignition temperature :	not applicable
Lower explosion limit :	no data available	Upper explosion limit :	no data available
Density (20 °C) :	ca. 1,17 g/cm ³	pH-value :	ca. 14
VOC (EG) :	0 Wt %	VOC (CH) :	0 Wt %

Storage

Keep container tightly closed. Keep/store only in original container. Protect against sub-zero temperatures. Optimized storage temperature is between 2 °C up to 35 °C. The product is storable in closed original packaging for at least 12 months. Starting date is the date of production.

Storage class (acc. TRGS 510): 8B

Disposal advices

The waste codes are recommendations based on the schedule use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances.

Waste code acc. EWC/AVV for unused product		Waste code acc. EWC/AVV for packaging	
07 06 01*	aqueous washing liquids and mother liquors	15 01 02	plastic packaging
20 01 29*	detergents containing dangerous substances.		

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

Order information

A50038	500 ml plastic bottle with trigger – TU: 20 x 500 ml (1 box)
A00138	1000 ml plastic bottle – TU: 12 x 1000 ml (1 box)
A02038	20 l Jerry can
A20038	200 l Drum